

Excellent Integrated System Limited





Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)
[HM2S30PE5101N9LF](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

Tous droits strictement réservés. Reproduction ou utilisation sans autorisation écrite du propriétaire. Propriété de c FCI. Droits de reproduction FCI.



PERFORMANCE CHARACTERISTICS

CURRENT RATING 1.5A AT 20°C (FULLY LOADED)
 1 A AT 70°C (FULLY LOADED)
 RATED VOLTAGE : 500 V AC (CONT /CONT)
 OPERATING TEMPERATURE : -55°C TO 125°C
 CONTACT RESISTANCE 20 MΩ MAX
 INSERTION FORCE : 0.75N MAX/CONT
 EXTRACTION FORCE : 0.15N MIN/CONT
 INSULATION RESISTANCE : 10⁴ MΩ MIN

- NOTES**
- " " LEAD FREE INDICATOR : LF=LEAD FREE
 " " PERFORMANCE LEVEL INDICATOR (REF DWG NO.BSC .201844.003)
 - THIS PRODUCT IS CSA APPROVED. THIS PRODUCT IS UL RECOGNIZED.
 - FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :BS.A.201572.001
 - THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

All rights strictly reserved. Reproduction or issue to third parties in any form without the written authority from the proprietor. Property of FCI. Copyright FCI.

Material		Spec ref	
Mat code		✓	
Heat treat		Tolerance IDEC# 2 IDEC SUSICA 1 IDEC ANGLESE 1 HOEREN	
Plating/Finish		projection ⊕	
Dr. M.Fret	31-10-97	size	A4
Eng		Scale	2.000
Chr		ECN	
Appr		REL Level	
Product family		BSC201907010	
Model Name		HM2S30PE5101	
Model Revision		E	
Title		MILLIPACS 2/TYPE C(W/O LOCK.PEG) SHIELDED	
Pro/E file		catalog no	
		HM2S30PE5101----	
		CUMSTOMER DRAWING	
		sheet 1 of 1	