

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Murata Electronics North America SFSCE10M7WF05-R0

For any questions, you can email us directly: sales@integrated-circuit.com



Distributor of Murata Electronics North America: Excellent Integrated System Limited

Datasheet of SFSCE10M7WF05-R0 - FILTER 10.7 MHZ 325 KHZ BAND SMD Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Part Numbering

Ceramic Filters (CERAFIL®) for IF

(Part Number)

SF	Р	KA	455K	D4A		-R0
SF	Е	CF	10M7	DF00	S0	-R0
0	2	3	4	6	6	7

●Product ID

2Oscillating/Element

Product ID			Oscillating/Element		
CF		U	4 Elements Area Expansion mode		
CF	Ceramic Filters	W	6 Elements Area Expansion mode		
		Р	4 Elements Area Expansion mode		
SF		Е	2 Elements Thickness Expansion mode		
		S	2 Elements Thickness Shear mode		

3Structure/Size

Code	Structure/Size
C□/K□	Chip Type
L 🗆	Lead Type

 \square is "A" or subsequent code, which indicates the size. It varies depending on vibration mode and number of elements. Chip type is only applied for **SF** series.

4 Nominal Center Frequency

Expressed by four-digit alphanumerics. The unit is hertz (Hz). If the unit is "kHz", it is expressed by three figures plus "K." If the unit is "MHz", a decimal point is expressed by the capital letter "M."

6Product Specification

Code	Product Specification		
D4A	Three-digit alphanumerics express pass bandwidth, center frequency tolerance and design type.		

SFE/S/J series are expressed by four-digit alphanumerics.

6Individual Specification

Code	Individual Specification Code
001	Expressed by three-digit alphanumerics.

SFE/S/J series are expressed by two-digit alphanumerics. With standard type, 6 is omitted.

Packaging

Code	Packaging
-B0	Bulk
-R0	Embossed Taping ø=180mm
-R1	Embossed Taping ø=330mm

Embossed taping is applied to chip type.