

# **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

<u>Digi International</u> 70001862

For any questions, you can email us directly: <a href="mailto:sales@integrated-circuit.com">sales@integrated-circuit.com</a>



#### Distributor of Digi International: Excellent Integrated System Limited

Datasheet of 70001862 - DEV SERVER SER-ETH DINRAIL MNTED

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com



INDUSTRIAL SERIAL SERVER

# DIGIONE® IA

Easy, reliable serial-to-Ethernet and Modbus-to-Modbus/TCP connectivity for industrial automation applications

Digi One IA provides reliable, cost-effective network connectivity for serial devices. This unobtrusive and easy-to-use serial server delivers serial-to-Ethernet connectivity to Programmable Logic Controllers (PLCs), Remote Terminal Units (RTUs), bar-code readers and other industrial devices.

Digi One IA supports most industrial automation protocols through TCP/UDP connections, serial bridging or COM port redirection using Digi's patented RealPort® software. RealPort enables existing applications to communicate with serial devices over the Ethernet. By creating a Modbus bridge,

multiple Modbus/TCP masters can share Modbus serial slaves, or Modbus serial masters can access Modbus/TCP slaves.

Digi One IA is easy to install locally or remotely. The IP address can be configured using DHCP, ARP-Ping or Setup, an application included with the installation CD that detects Digi One devices on the network. Using the web interface, users can configure advanced functions into their application.

#### **BENEFITS**

- Patented RealPort for COM/TTY port control and management
- TCP/UDP Socket Services for broad device connectivity and application use
- Modbus serial to Modbus/TCP protocol conversion
- Switch selectable RS-232/422/485 for simple interfacing to any type of serial device
- Industrial DIN rail mounting for use in spaceprohibitive control cabinets
- Galvanic isolation (between power and serial)
- Tunable for low latency or optimized throughput

#### **RELATED PRODUCTS**







DigiOne® SP IA





# APPLICATION EXAMPLE: INDUSTRIAL AUTOMATION






### Distributor of Digi International: Excellent Integrated System Limited


Datasheet of 70001862 - DEV SERVER SER-ETH DINRAIL MNTED

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

SPECIFICATIONS	Digi One® IA
FEATURES	
MANAGEMENT	HTTP configuration, Digi Port Authority - Remote management diagnostics and auto-discovery tool
PROTOCOLS	Telnet, Reverse Telnet and extended Telnet RFC 2217; TCP/UDP Socket Services; UDP, support 32 concurrent socket connections; DHCP/RARP, ARP-Ping; Modbus ASCII/RTU to Modbus TCP conversion; Modbus Ethernet-to-Serial Bridge Function supporting Modbus/TCP, Modbus/UDP, Modbus/RTU, Modbus/ASCII; Modbus bridge supports TCP and UDP Encapsulation of Modbus/RTU, Modbus/ASCII
SOFTWARE	Patented RealPort for COM/TTY ports
OPERATING SYSTEMS	AIX, HP-UX, Solaris, Linux®, Windows® 2000, Windows® XP, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10, Windows Server® 2003, Windows Server® 2012. Note: TCP/UDP socket services are operating system independent
STATUS LEDS	Serial signals, Power, Ethernet, Diagnostics
DIMENSIONS (L X W X D)	4.70 in x 0.90 in x 4.0 in (12.00 cm x 2.30 cm x 10.10 cm)
WEIGHT	2.25 oz (64.00 g)
OTHER	Full modem and hardware flow control, Flash upgradeable firmware, 35 mm DIN rail mounting
INTERFACES	
SERIAL PORTS	1 RS-232/422/485 (switch selectable)
SERIAL CONNECTOR	DB-9M or screw terminal connectors
SERIAL THROUGHPUT	Up to 230 Kbps
ETHERNET PHYSICAL LAYER	10/100 Base-T
POWER REQUIREMENTS	
POWER INPUT	9-30 VDC @ .5 Amps max
POWER CONNECTOR	Screw terminal block power jack for external supply
PRODUCT SURGE PROTECTION (ESD)	2 kV isolation between power supply and serial ground
ENVIRONMENTAL	
OPERATING TEMPERATURE	0° C to 60° C (32° F to 140° F)
RELATIVE HUMIDITY	5% to 90% (non-condensing)
ETHERNET ISOLATION	1500 VAC min per IEEE 802.3/ANSI X3.263
SERIAL PORT PROTECTION (ESD)	15 kV human body model
REGULATORY APPROVALS	
SAFETY	UL 60950, UL1604 (Class 1 Div 2), EN60950, CAN/CSA C22.2 No.60950
EMISSIONS/IMMUNITY	FCC Part 15 Subpart B (Class A), EN55024, EN55022 (Class A), EN61000-6-2

# PART NUMBERS DESCRIPTION 70001862 Digi One IA





91001156

F1/915



**DIGI SERVICE AND SUPPORT** / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

@ 1996-2015 Digi International Inc. All rights reserved. All trademarks are the property of their respective owners.

DIGI INTERNATIONAL WORLDWIDE HQ 877-912-3444 / 952-912-3444 / www.digi.com

**DIGI INTERNATIONAL FRANCE** +33-1-55-61-98-98 / www.digi.fr

**DIGI INTERNATIONAL JAPAN** +81-3-5428-0261 / www.digi-intl.co.jp DIGI INTERNATIONAL SINGAPORE +65-6213-5380

**DIGI INTERNATIONAL CHINA** +86-21-50492199 / www.digi.com.cn

