

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Switchcraft Inc.](#)
[LF1PX](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

**NPB
559****Switchcraft®
1/4" Longframe Patchcords**

PRELIMINARY

**1/4"
Longframe
Single
Patchcords**

Introducing Switchcraft's re-designed 3-conductor 1/4" Longframe audio patchcords. Now made with a low capacitance 110 Ohm cable it is ideal not only for analog applications but also for digital AES/EBU audio and SMPTE time code patching. The overall flexible jacket is available in eight attractive colors. The overmolded rubber flex handle-boot

reduces strain off the cable when pulled or tugged. The overmold covers a metallic shell which greatly reduces crosstalk. The nickel plated plugs ends are non-tarnishing as well as self cleaning when used with Switchcraft MT series patchbays.

Switchcraft®

www.switchcraft.com

5555 North Elston Avenue/Chicago, IL. 60630
Phone: 773-792-2700 Fax: 773-792-2129


Made in the U.S.A.

High Performance Audio Patchcords

Broadcast Series

1/4" Longframe Analog and Digital Audio Patchcords

Part Numbering System



Colors	Color Code	Standard Foot Lengths
		1'
Black =	BK	2'
Red =	R	3'
Orange =	O	4'
Yellow =	Y	5'
Green =	GN	6'
Blue =	BL	7'
Purple =	P	8'
Gray =	GY	9'
		10'

Custom lengths are available by request.
1 meter is equal to 3.28 feet.

SPECIFICATIONS:

- * Mil Spec Series: M642
- * Standard plug terminations are 1/4" Longframe
Plug handle is molded thermoplastic.
- * Plugs: Tip Rod, Ring and Sleeve - Copper Alloy
- * Cable: 26 AWG (30x40) OFBC, 110 Ohm Low Capacitance Jacket is Matte PVC