

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[PUI Audio, Inc.](#)  
[AS07008PS-WR-R](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

SPECIFICATIONS			THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED. ©2003, Projects Unlimited Inc.	REVISION HISTORY			
PARAMETERS	VALUES	UNITS		LTR	DESCRIPTION	DATE	APPROVED
RATED INPUT POWER	2	W	-	RELEASED FROM ENGINEERING	9/25/2006		
MAX INPUT POWER	4	W	A	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	1/26/2009	B.R.	
IMPEDANCE	8 ± 15%	OHM					
OUTPUT SPL @ 1W/1M (AT 0.6, 0.8, 1.0, 1.2, 1.5 kHz)	86 ± 3	dB					
DISTORTION (MAX.)	7%	-					
RESONANT FREQUENCY	300 ± 20%	Hz					
FREQUENCY RANGE	300 ~ 20,000	Hz					
HOUSING MATERIAL	METAL	-					
CONE MATERIAL	TREATED PAPER	-					
MAGNET MATERIAL	FERRITE	-					
OPERATING TEMPERATURE	-25 ~ +55	°C					
WEIGHT	143	grams					

  
  

**NOTES:**

- ALL DIMENSIONS ARE IN MILLIMETERS.
- SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- THIS PART IS RoHS 2002/95/EC COMPLIANT.
- Δ4. CONE HAS BEEN TREATED FOR WATER RESISTANCE.

  

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.	SIZE	Designed by	Date	Checked by	Date	Approved by	Date	Drawn Date	
	A3	J.D.	9/25/2006	B.R.	9/25/2006	R.W.	9/25/2006	1/26/2009	
AS07008PS-WR-R.idw				AS07008PS-WR-R				Speaker	
							Edition	Sheet	
							-	1 / 1	