

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ON Semiconductor](#)

[BU22](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# BUV22

## SWITCHMODE™ Series NPN Silicon Power Transistor

This device is designed for high speed, high current, high power applications.

### Features

- High DC Current Gain:  
 $h_{FE} \text{ min} = 20 \text{ at } I_C = 10 \text{ A}$
- Low  $V_{CE(sat)}$ ,  $V_{CE(sat)}$   
 $\text{max} = 1.0 \text{ V at } I_C = 10 \text{ A}$
- Very Fast Switching Times:  
 $TF \text{ max} = 0.35 \mu\text{s at } I_C = 20 \text{ A}$
- Pb-Free Package is Available\*

### MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	$V_{CEO(SUS)}$	250	Vdc
Collector–Base Voltage	$V_{CBO}$	300	Vdc
Emitter–Base Voltage	$V_{EBO}$	7	Vdc
Collector–Emitter Voltage ( $V_{BE} = -1.5 \text{ V}$ )	$V_{CEX}$	300	Vdc
Collector–Emitter Voltage ( $R_{BE} = 100 \Omega$ )	$V_{CER}$	290	Vdc
Collector–Current – Continuous	$I_C$	40	Adc
– Peak ( $PW \leq 10 \text{ ms}$ )	$I_{CM}$	50	Apk
Base–Current Continuous	$I_B$	8	Adc
Total Device Dissipation @ $T_C = 25^\circ\text{C}$	$P_D$	250	W
Operating and Storage Junction Temperature Range	$T_J, T_{stg}$	-65 to 200	$^\circ\text{C}$

### THERMAL CHARACTERISTICS

Characteristics	Symbol	Max	Unit
Thermal Resistance, Junction–to–Case	$\theta_{JC}$	0.7	$^\circ\text{C/W}$


Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.



**ON Semiconductor®**

<http://onsemi.com>

**40 AMPERES  
NPN SILICON POWER  
METAL TRANSISTOR  
250 VOLTS – 250 WATTS**



**TO-204AE (TO-3)  
CASE 197A**

### MARKING DIAGRAM



BUV22 = Device Code  
G = Pb-Free Package  
A = Assembly Location  
Y = Year  
WW = Work Week  
MEX = Country of Origin

### ORDERING INFORMATION

Device	Package	Shipping
BUV22	TO-204	100 Units / Tray
BUV22G	TO-204 (Pb-Free)	100 Units / Tray

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## BUV22

### ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
<b>OFF CHARACTERISTICS</b> (Note 1)				
Collector–Emitter Sustaining Voltage (I <sub>C</sub> = 200 mA, I <sub>B</sub> = 0, L = 25 mH)	V <sub>CEO(sus)</sub>	250		Vdc
Collector Cutoff Current at Reverse Bias (V <sub>CE</sub> = 300 V, V <sub>BE</sub> = -1.5 V) (V <sub>CE</sub> = 300 V, V <sub>BE</sub> = -1.5 V, T <sub>C</sub> = 125°C)	I <sub>CEX</sub>		3.0 12.0	mAdc
Collector–Emitter Cutoff Current (V <sub>CE</sub> = 200 V)	I <sub>CEO</sub>		3.0	mAdc
Emitter–Base Reverse Voltage (I <sub>E</sub> = 50 mA)	V <sub>EBO</sub>	7		V
Emitter–Cutoff Current (V <sub>EB</sub> = 5 V)	I <sub>EBO</sub>		1.0	mAdc

### SECOND BREAKDOWN

Second Breakdown Collector Current with base forward biased (V <sub>CE</sub> = 20 V, t = 1 s) (V <sub>CE</sub> = 140 V, t = 1 s)	I <sub>S/b</sub>	12 0.15		Adc
--	------------------	------------	--	-----

### ON CHARACTERISTICS

 (Note 1)

DC Current Gain (I <sub>C</sub> = 10 A, V <sub>CE</sub> = 4 V) (I <sub>C</sub> = 20 A, V <sub>CE</sub> = 4 V)	h <sub>FE</sub>	20 10	60	
Collector–Emitter Saturation Voltage (I <sub>C</sub> = 10 A, I <sub>B</sub> = 1 A) (I <sub>C</sub> = 20 A, I <sub>B</sub> = 2.5 A)	V <sub>CE(sat)</sub>		1.0 1.5	Vdc
Base–Emitter Saturation Voltage (I <sub>C</sub> = 40 A, I <sub>B</sub> = 4 A)	V <sub>BE(sat)</sub>		1.5	Vdc

### DYNAMIC CHARACTERISTICS

Current Gain — Bandwidth Product (V <sub>CE</sub> = 15 V, I <sub>C</sub> = 2 A, f = 4 MHz)	f <sub>T</sub>	8.0		MHz
---	----------------	-----	--	-----

### SWITCHING CHARACTERISTICS

 (Resistive Load)

Turn–on Time	(I <sub>C</sub> = 20 A, I <sub>B1</sub> = I <sub>B2</sub> = 2.5 A, V <sub>CC</sub> = 100 V, R <sub>C</sub> = 5 Ω)	t <sub>on</sub>	0.8	μs
Storage Time		t <sub>s</sub>	2.0	
Fall Time		t <sub>f</sub>	0.35	

1. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.




Figure 1. Power Derating

### BUV22




Figure 2. Active Region Safe Operating Area

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate  $I_C - V_{CE}$  limits of the transistor that must be observed for reliable operation i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 2 is based on  $T_C = 25^\circ\text{C}$ ;  $T_{J(pk)}$  is variable depending on power level. Second breakdown limitations do not derate the same as thermal limitations.

At high case temperatures, thermal limitations will reduce the power that can handled to values less than the limitations imposed by second breakdown.




Figure 3. "On" Voltages




Figure 4. DC Current Gain




Figure 5. Resistive Switching Performance






Figure 6. Switching Times Test Circuit

## BUV22

### PACKAGE DIMENSIONS


TO-204 (TO-3)  
CASE 197A-05  
ISSUE K



- NOTES:  
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.  
2. CONTROLLING DIMENSION: INCH.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	1.530 REF		38.86 REF	
B	0.990	1.050	25.15	26.67
C	0.250	0.335	6.35	8.51
D	0.057	0.063	1.45	1.60
E	0.060	0.070	1.53	1.77
G	0.430 BSC		10.92 BSC	
H	0.215 BSC		5.46 BSC	
K	0.440	0.480	11.18	12.19
L	0.665 BSC		16.89 BSC	
N	0.760	0.830	19.31	21.08
Q	0.151	0.165	3.84	4.19
U	1.187 BSC		30.15 BSC	
V	0.131	0.188	3.33	4.77

SWITCHMODE is a trademark of Semiconductor Components Industries, LLC.

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

#### PUBLICATION ORDERING INFORMATION

##### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA  
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your local Sales Representative.