

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Schurter](#)
[0031.1663](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Accessories

www.schurter.com/Z02

Caps to FEU, FAU, FAC

Caps to Holder FEU, FEU (Med), FAU, FAC



250 VAC · 4W/16A (VDE) · 600VAC/DC · 16A (UL/CSA)



Standards

- IEC 60127-6
- UL 4248-1 / UL 512
- CSA 4248-1 / no. 39

Approvals

- VDE Certificate Number: 134125
- UL File Number: E39328

References

Mating Cap to [FAC](#); [FAU](#); [FEU](#); [FEU \(Med\)](#); [SWG](#)

Weblinks


[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [REACH](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

Technical Data

Fuse-Link	5 x 20 or 6.3 x 32 mm
Rated Voltage	250VAC (VDE), 600VAC/DC (UL/CSA)
Rated current	10A (VDE), 16A (UL/CSA)
Rated Power Acceptance IEC	4W / 16A @ Ta 23°C
Degree of Protection	IP 40
Admissible Ambient Air Temp.	-40°C to 85°C
Material: Cap	Thermoplastic, UL 94V-0
Storage Conditions	0°C to 60°C, max. 70% r.h.
Product Marking	

Contact Resistance	< mΩ at 20 mV
--------------------	---------------

Dimension



0031.1663

0031.1661, 0031.1666

All Variants

Cap	Fuse-Link	Degree of Protection	Colour Cap	Order Number
slotted	6.3 x 32mm	IP 40	black	0031.1661
slotted	5 x 20mm	IP 40	black	0031.1663
slotted	6.3 x 32mm	IP 40	grey	0031.1666

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/Stock-Check/Stock-Check-SCHURTER>

Packaging Unit

Plastic Bag (100 pcs.)