

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Tripp Lite](#)
[U209-004](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Tripp Lite
 1111 W. 35th Street
 Chicago, IL 60609 USA
 Telephone: 773.869.1234
 www.tripplite.com

4-Port USB to Serial Adapter (USB-A Male to 4x DB9M)

MODEL NUMBER: **U209-004**



Description

Tripp Lite's USB to serial adapter enables up to 4 serial devices (RS-232) to be connected to a computer through a single USB port. Perfect for applications where there are insufficient or no serial ports available. Use with serial devices such as touch screen monitors, digital cameras, card readers and printers. Each channel is capable of functioning at a 460.8 Mbps data transfer rate. A CD with drivers is included (Windows 98, ME, 2000, NT, XP). Plug-and-play/hot-swappable allows you to add or remove a device at any time. Does not require any external power. Tripp Lite warrants this product to be free from defects in materials and workmanship for 5 years.

Features

- Connect a PDA, digital camera, modem or ISDN terminal to a computer through a USB port
- Upgrades a traditional RS-232 serial port to USB
- Connectors: USB-A male/(4x) DB9 male
- Comes standard with 16550 universal asynchronous receiver/transmitters (UART's) containing 16 byte first-in- first-out (FIFO) storage devices. This in conjunction with the USB micro controller FIFO's, helps relieve the CPU of excess interrupts by buffering both the received and transmitted data
- Does not require external power
- Plug-and-play/hot-swappable allows you to add or remove a device at any time
- Supports data transfer rates over 460.8Mbps
- Supports DB25 serial devices by connecting Tripp Lite's AT serial gold adapter (# P100-000)
- Compatible with Windows 98/SE, ME, NT, 2000 and XP
- CD with drivers included

Highlights

- Connect up to 4 serial devices (RS-232) through a single USB port
- Plug-and-play design
- No external power needed

System Requirements

- Available USB port on the PC (it is recommended to connect adapter directly to the PC and not through a USB HUB).
- CD-ROM to load drivers from supplied CD onto PC

Package Includes

- USB to Serial Adapter USB-A to DB9M
- Driver CD
- Serial Port Tester

Specifications

PHYSICAL	
Color	Beige



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

CONNECTIONS	
Ports	4
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	DB9 (MALE)

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>