

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[CUI Inc.](#)

[EPA240050-S/T-SZ](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Part No: EPA240050-S/T-SZ

Description: linear power supply

Date: 5/11/2007

Unit: mm

Page No: 1 of 7



Specifications

Output voltage	24 V ac at 500 mA	
Rated input voltage	120 V ac	
Primary rated voltage	120 V ac 60 Hz 18 W	
Primary exciting current	30 mA rms max.	
Secondary rated voltage & current	no load voltage (max.)	30.3 V ref
	full load voltage (500 mA)	24 V $\pm 5\%$
Temperature rise of primary winding (full load)	70°C max. using resistance method	
Insulation resistance	≥ 100 M Ohm at 500 V dc	
HI-POT test	from input to output for 1 min.	1240 V ac at 2 mA
	from input to output for 1 sec.	1600 V ac at 2 mA
	from primary to secondary winding for 1 sec.	1600 V ac at 2 mA
	from primary winding to core for 1 sec.	1600 V ac at 2 mA
	from secondary winding to core for 1 sec.	750 V ac at 2 mA
Safety standards	UL/cUL	
RoHS compliant	yes	
No load power consumption	0.5 W max.	
Efficiency	Energy Star Compliant - Efficiency Level IV	
Test conditions	Ambient temp	40°C $\pm 2^\circ\text{C}$
	Humidity	90-95% 96 hours at Full Load
	Rated voltage	8 hours at full load
Adapter color	Case	black
	Cord	black



CUI INC

Part No: EPA240050-S/T-SZ


Description: linear power supply

Date: 5/11/2007

Unit: mm

Page No: 2 of 7

Label





Part No: EPA240050-S/T-SZ

Description: linear power supply

Date: 5/11/2007


Unit: mm

Page No: 3 of 7

Mechanical Drawing

Tolerance: ± 1

Weight 419 g





CUI INC

Part No: EPA240050-S/T-SZ


Description: linear power supply

Date: 5/11/2007

Unit: mm

Page No: 4 of 7

DC Cord



#24AWGX2C BLACK/WHITE WIRE BLACK WIRE IN NEGATIVE, BLACK/WHITE WIRE IN POSITIVE
WIRE OD: Ø1.8X3.6

VIBRATION TEST	a. ±60°
	b. WEIGHT 200g
	c. 40 ROUND/MINUTE
	d. OVER 1000 COUNT MIN



Part No: EPA240050-S/T-SZ


Description: linear power supply

Date: 5/11/2007


Unit: mm

Page No: 5 of 7

Circuit Diagrams



Test Diagram





CUI INC

Part No: EPA240050-S/T-SZ

Description: linear power supply



Date: 5/11/2007

Unit: mm

Page No: 6 of 7

Individual Packaging

Tolerance: ± 1





Part No: EPA240050-S/T-SZ

Description: linear power supply

Date: 5/11/2007

Unit: mm

Page No: 7 of 7

Packaging

Tolerance: +7/-0

OUTSIDE CARTON: A=B(6mm)

INSIDE CARTON: A-B(3mm)

CARTON SIZE: 430x223x269mm

Q'TY: 40pcs(10X4X1)

N.W: 16.8 KGS

G.W: 17.8 KGS

N.W: 18.8 KGS

