

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Wurth Electronics Inc 742792036

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



more than you expect

B Recommended land pattern: [mm] A Dimensions: [mm] WÜRTH ELEKTRONĬK W 1,2 **D Electrical Properties:** Test conditions Value Unit Properties Tol. Impedance @ 100 MHz 100 MHz 470 Ω ±25% 0,5 ±0,3 190 MHz Maximum impedance Ζ 560 Ω typ. Rated current $\Delta T = 20K$ I_{R} 200 mΑ max. 0,9 ±0,2 W = 4.0DC Resistance 0.30 Ω max. R_{DC} 2,0 ±0,2 Scale - 10:1 Wide Band Туре C Schematic: E General information: Do not use this part beyond the Rated Current, as this will create excessive heat and can harm the component •Storage Temperature (on Tape & Reel): -20°C to 60°C •Operating Temperature: -55°C to 125°C •Test conditions of Electrical Properties: 20°C, 33% RH if not specified differently Scale - 10:1 DESCRIPTION Projection 5.7 2014-06-05 SSt SSt - = 05.6 2013-12-18 SSt SSt **WE-CBF SMD EMI Suppression Ferrite** Würth Elektronik elSos GmbH & Co. KG EMC & Inductive Solutions Max-EyHr-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com elSos@we-online.com 5.5 2013-04-17 SSt SSt Bead 2012-11-28 SSt SSt 5.4 Order - No COMPLIANT ROHS&REACH WORTH ELEKTRONIK 5.3 2012-10-23 SSt SMu SIZE SSt SMu 5.2 2012-09-26 742792036 SSt SSt Δ. 2012-06-26 5.1 RFV DATE BY CHECKED Size: 0805


The electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized for use in equipment specifically governing such usage. Moreover Wild's Existence is a single standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such usage. Moreover Wild's Existence is a single standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.




more than you expect



F1 Typical Impedance Characteristics:





				Projection .		DESCRIPTION		
5.7	2014-06-05	SSt	SSt	-E-1-@-				
5.6	2013-12-18	SSt	SSt			WE-CBF SMD E	EMI Suppression Ferrite	
5.5	2013-04-17	SSt	SSt	Würth Elektronik eiSos Gmbl	H & Co. KG	Bead		
5.4	2012-11-28	SSt	SSt	EMC & Inductive Solutions Max-Evth-Str. 1		Deau		
5.3	2012-10-23	SSt	SMu	74638 Waldenburg		Order No.	COMPLIANT	SIZE
5.2	2012-09-26	SSt	SMu	Germany Tel. +49 (0) 79 42 945 - 0			UILL	
5.1	2012-06-26	SSt	SSt	www.we-online.com eiSos@we-online.com		742792036		A4
REV	DATE	BY	CHECKED			Size: 0805		

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover With Elektronik eSis Enrich & D. KS products is not authorized for use in requirement state or india state or india state in a state and in a state in the design of the state in the design o



in stage. In addition, suffic


more than you expect

G Packaging Specification - Tape and Reel [mm]:

nic comp

verv e

ient which is used in electr






H Soldering Specifications:



H1: Classification Reflow Profile for SMT components:



H2: Classification Reflow Profiles

Profile Feature	Pb-Free Assembly		
Preheat - Temperature Min (T _{smin}) - Temperature Max (T _{smax}) - Time (t _s) from (T _{smin} to T _{smax})	150°C 200°C 60-120 seconds		
Ramp-up rate (T _L to T _P)	3°C/ second max.		
Liquidous temperature (TL) Time (tL) maintained above TL	217°C 60-150 seconds		
Peak package body temperature (Tp)	See Table H3		
Time within 5°C of actual peak temperature (t_{p})	20-30 seconds		
Ramp-down rate (T _P to T_L)	6°C/ second max.		
Time 25°C to peak temperature	8 minutes max.		
refer to IPC/ IEDEC. I-STD-020D			

refer to IPC/JEDEC J-STD-020D

H3: Package Classification Reflow Temperature

	Package Thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
PB-Free Assembly	< 1.6 mm	260°C	260°C	260°C
PB-Free Assembly	1.6 - 2.5 mm	260°C	250°C	245°C
PB-Free Assembly	≥ 2.5 mm	250°C	245°C	245°C

refer to IPC/JEDEC J-STD-020D

				Projection ,		DESCRIPTION		
5.7	2014-06-05	SSt	SSt	-E-1-@-				
5.6	2013-12-18	SSt	SSt			WE-CBF SMD EI	WI Suppression Ferrite	,
5.5	2013-04-17	SSt	SSt	Würth Elektronik elSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +40 (V72) 42 045 0		Bead		
5.4	2012-11-28	SSt	SSt					
5.3	2012-10-23	SSt	SMu			Order No.	COMPLIANT	SIZE
5.2	2012-09-26	SSt	SMu			74070000	ROHS&REACh	OILL
5.1	2012-06-26	SSt	SSt	www.we-online.com eiSos@we-online.com				A4
REV	DATE	BY	CHECKED	CIGUS/WWC-UTIHIC.CUTI		Size: 0805		

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard standard is specially required or where a higher safety standard and reliability standard and reliability standard standard is specially required or where a higher safety standard and reliability standard standard is specially required or where a higher safety standard and reliability standard standard is specially required or where a higher safety standard and reliability standard standard is specially required or where a higher safety standard and reliability standard standard is specially required or where a higher safety standard and reliability standard standard is specially required or where a higher safety standard and reliability standard standard is specially required or where a higher safety standard and reliability standard standard is specially required or where a higher safety standard and reliability standard stan

L

I Cautions and Warnings:

The following conditions apply to all goods within the product series of WE-CBF of Würth Elektronik eiSos GmbH & Co. KG:

General:

All recommendations according to the general technical specifications of the data sheet have to be complied with.

The usage and operation of the product within ambient conditions, which probably alloy or harm the component surface, has to be avoided.

If the product is potted in customer applications, the potting material might shrink during and after hardening. The product is exposed to the pressure of the potting material with the effect that the ferrite body and termination is possibly damaged by this pressure and so the electrical as well as the mechanical characteristics are endangered to be affected. After the potting material is cured, the ferrite body and termination of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply to customer specific products.

Cleaning agents that are used to clean the customer application might damage or change the characteristics of the component, body, pins or termination

Direct mechanical impact to the product shall be prevented as the ferrite material of the ferrite body could flake or in the worst case it could break

Product specific: Follow all instructions mentioned in the data sheet, especially:

•The soldering profile has to be complied with according to the technical reflow soldering specification, otherwise this will void the

warranty. · Wave soldering is only allowed after evaluation and approval

•All products shall be used before the end of the period of 12 months based on th product date code, if not a 100% solderability can't be ensured.

. Violation of the technical product specifications such as exceeding the nominal rated current will void the warranty

The general and product specific cautions comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable; however, no responsibility is assumed for inaccuracies or incompleteness

				Projection		DESCRIPTION			
5.7	2014-06-05	SSt	SSt						
5.6	2013-12-18	SSt	SSt	$\Box \Psi$		WE-CBF SMD EMI Suppression Ferrite			
5.5	2013-04-17	SSt	SSt	Würth Elektronik elSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg		Bead			
5.4	2012-11-28	SSt	SSt						
5.3	2012-10-23	SSt	SMu			Order No.	COMPLIANT	SIZE	
5.2	2012-09-26	SSt	SMu	Germany Tel. +49 (0) 79 42 945 - 0			ROHS&REACh	OILL	
5.1	2012-06-26	SSt	SSt	www.we-online.com eiSos@we-online.com		742792036		A4	
REV	DATE	BY	CHECKED	elsus/e/we-online.com		Size: 0805			

lectronic equipment only. This product is not authorized for use in equipment where a higher safety standard an erabality standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use, intended for use in areas such as military, aerospace, aution, muchar control, abmannie, transportation signal, disaster prevention, medical, public information network etc. Want Elektronik eSSs GmbH & Co KS must be informed about the intent of such usage before to performed on very electronic component which is used in electrical circuits art requesting high functions or performance. electronic component has been designed and developed for usage in general electronic e over Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended fr esign-in stage. In addition, sufficient reliability evaluation checks for safety must be perfor the design-in stage. In addition, sufficient r



more than you expect

J Important Notes:

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibi-lity for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications

In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger thrman life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component.

Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected

6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a stan-dard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered.

The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG.

Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

				Projection		DESCRIPTION		
5.7	2014-06-05	SSt	SSt					
5.6	2013-12-18	SSt	SSt			WE-CBF SMD EM	VI Suppression Ferrite	e
5.5	2013-04-17	SSt	SSt	Würth Elektronik eiSos Gmbl	H & Co. KG	Bead		
5.4	2012-11-28	SSt	SSt	EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg		Deau		
5.3	2012-10-23	SSt	SMu			Order No.	COMPLIANT	SIZE
5.2	2012-09-26	SSt	SMu	Germany Tel. +49 (0) 79 42 945 - 0		74070000	ROHS&REACh	ULL
5.1	2012-06-26	SSt	SSt	www.we-online.com eiSos@we-online.com		742792036 VORTH ELEKTR		A4
REV	DATE	BY	CHECKED	elsus@we-unime.com		Size: 0805		

Her safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use, transportation (automotive control, train control, stan portation signal, disaster prevention, medical, public information network etc... Wurth Elektronik eSos GmbH & Co KG must be informed about the internit of such usage before in pills safety and reliability functions or performance. nent has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a high ronik eSSS smbH & Co KG products are neither designed nor intended for use in areas such as military, aerospoe, avlaton, nuclear control, submarine additon, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that reg in stage. In addition, sufficien

