

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[IXYS Corporation](#)

[DSEP2X35-06C](#)

For any questions, you can email us directly:


sales@integrated-circuit.com

HiPerDynFRED™ Epitaxial Diode with soft recovery


$I_{FAV} = 2x35\text{ A}$
 $V_{RRM} = 600\text{ V}$
 $t_{rr} = 20\text{ ns}$

Preliminary Data

V_{RSM}	V_{RRM}	Type
V	V	
600	600	DSEP 2x 35-06C



SOT-227 B,
miniBLOC



Symbol	Test Conditions	Maximum Ratings	
I_{FRMS}		100	A
I_{FAVM}	$T_C = 100^\circ\text{C}$; rectangular, $d = 0.5$	35	A
I_{FRM}	$t_p < 10\ \mu\text{s}$; rep. rating, pulse width limited by T_{VJM}	tbd	A
I_{FSM}	$T_{VJ} = 45^\circ\text{C}$; $t_p = 10\text{ ms}$ (50 Hz), sine	300	A
E_{AS}	$T_{VJ} = 25^\circ\text{C}$; non-repetitive $I_{AS} = 3\text{ A}$; $L = 180\ \mu\text{H}$	1.2	mJ
I_{AR}	$V_A = 1.5 \cdot V_R$ typ.; $f = 10\text{ kHz}$; repetitive	0.3	A
T_{VJ}		-40...+150	$^\circ\text{C}$
T_{VJM}		150	$^\circ\text{C}$
T_{stg}		-40...+150	$^\circ\text{C}$
P_{tot}	$T_C = 25^\circ\text{C}$	210	W
V_{ISOL}	50/60 Hz, RMS, $I_{ISOL} \leq 1\text{ mA}$	2500	V~
M_d	mounting torque (M4)	1.1-1.5/9-13	Nm/lb.in.
	terminal connection torque (M4)	1.1-1.5/9-13	Nm/lb.in.
Weight	typical	30	g

Features

- International standard package miniBLOC
- Isolation voltage 2500 V~
- UL registered E 72873
- 2 independent FRED in 1 package
- Planar passivated chips
- Very short recovery time
- Extremely low switching losses
- Low I_{RM} -values
- Soft recovery behaviour

Applications

- Antiparallel diode for high frequency switching devices
- Antisaturation diode
- Snubber diode
- Free wheeling diode in converters and motor control circuits
- Rectifiers in switch mode power supplies (SMPS)
- Inductive heating
- Uninterruptible power supplies (UPS)
- Ultrasonic cleaners and welders

Advantages

- Avalanche voltage rated for reliable operation
- Soft reverse recovery for low EMI/RFI
- Low I_{RM} reduces:
 - Power dissipation within the diode
 - Turn-on loss in the commutating switch

Dimensions see Outlines.pdf

Symbol	Test Conditions	Characteristic Values	
		typ.	max.
I_R ①	$V_R = V_{RRM}$; $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 150^\circ\text{C}$	0.25	1.0
			mA
V_F ②	$I_F = 35\text{ A}$; $T_{VJ} = 125^\circ\text{C}$ $T_{VJ} = 25^\circ\text{C}$	1.97	2.50
			V
R_{thJC}	with heatsink compound	0.1	0.6
R_{thCH}			K/W
t_{rr}	$I_F = 1\text{ A}$; $-di/dt = 300\text{ A}/\mu\text{s}$; $V_R = 30\text{ V}$; $T_{VJ} = 25^\circ\text{C}$	20	ns
I_{RM}	$V_R = 100\text{ V}$; $I_F = 50\text{ A}$; $-di_F/dt = 100\text{ A}/\mu\text{s}$ $T_{VJ} = 100^\circ\text{C}$	4.5	7.0
			A

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %
 ② Pulse Width = 300 μs , Duty Cycle < 2.0 %

Data according to IEC 60747 and per diode unless otherwise specified

**Recommended replacement:
2x DPH30IS600HI**