Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

IXYS Corporation
VCO132-08IO7

For any questions, you can email us directly:
sales@integrated-circuit.com

Distributor of IXYS Corporation: Excellent Integrated System Limited
Datasheet of VCO132-08IO7 - MOD THYRISTOR 800V 130A ECO-PAC2
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

IXYS | Advanced Technical Information | **VCO132**

Thyristor Modules

ECO-PAC 2

I_{TRMS} = 200A
I_{TAVM} = 130A
V_{RRM} = 800-1800 V

V_{RSM} V_{DSM} V	V_{RRM} V_{DRM} V	Typ
900	800	VCO 132 - 08io7
1300	1200	VCO 132 - 12io7
1500	1400	VCO 132 - 14io7
1700	1600	VCO 132 - 16io7
1900	1800	VCO 132 - 18io7



Symbol	Conditions		Maximum Ratings	
I_{TRMS}			200	A
I_{TAVM}	T_C = 85°C; T_{VJ} = 130°C; 180° sine		130	A
I_{TSM}	T_{VJ} = 45°C; V_R = 0 V;	t = 10 ms (50 Hz), sine	3600	A
		t = 8.3 ms (60 Hz), sine	3850	A
	T_{VJ} = 125°C; V_R = 0 V;	t = 10 ms (50 Hz), sine	3200	A
		t = 8.3 ms (60 Hz), sine	3420	A
I^2dt	T_{VJ} = 45°C; V_R = 0 V;	t = 10 ms (50 Hz), sine	64800	A^2s
		t = 8.3 ms (60 Hz), sine	62300	A^2s
	T_{VJ} = 125°C; V_R = 0 V;	t = 10 ms (50 Hz), sine	51200	A^2s
		t = 8.3 ms (60 Hz), sine	49100	A^2s
$(di/dt)_{cr}$	T_{VJ} = 125°C; f = 50 Hz; t_P = 200 µs; $V_D = {}^2/_3 V_{DRM}$;	repetitive, I_T = 250 A	150	A/µs
	I_G = 0.5 A di_G/dt = 0.5 A/µs;	non repetitive, $I_T = I_{TAVM}$	500	A/µs
$(dv/dt)_{cr}$	T_{VJ} = 125°C; $V_{DR} = {}^2/_3 V_{DRM}$ $R_{GK} = \infty$, method 1 (linear voltage rise)		1000	V/µs
P_{GM}	T_{VJ} = 125°C; $I_T = I_{TAVM}$;	t_P = 30 ms	≤ 10	W
		t_P = 300 ms	≤ 5	W
P_{GAVM}			0.5	W
V_{RGM}			10	V
T_{VJ}			-40 ... + 130	°C
T_{VJM}	for 10 sec		150	°C
T_{stg}			-40 ... + 125	°C
V_{ISOL}	50/60 Hz, RMS I_{ISOL} ≤ 1 mA	t = 1 min	3000	V ~
		t = 1 s	3600	V ~
M_d	Mounting torque	(M4)	1.5 - 2.0	Nm
			14 - 18	lb.in.
Weight	typ.		24	g

Data according to IEC 60747 refer to a single thyristor unless otherwise stated

Features

- Isolation voltage 3600 V~
- Planar glass passivated chips
- Low forward voltage drop
- Leads suitable for PC board soldering

Applications

- DC motor control
- Light and temperature control
- Softstart AC motor controller
- Solid state switches

Advantages

- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling
- High power density
- Small and light weight

IXYS reserves the right to change limits, test conditions and dimensions.

312

© 2003 IXYS All rights reserved

IXYS Advanced Technical Information **VCO132**

Component

Symbol	Conditions	Characteristic Values min.	typ.	max.	
I_D, I_R	T_{VJ} = 125°C; $V_R = V_{RRM}$; $V_D = V_{DRM}$			10	mA
V_T	I_T = 200 A; T_{VJ} = 25°C			1.3	V
V_{TO} r_T	For power-loss calculations only			0.8 1.65	V mΩ
V_{GT}	V_D = 6 V; T_{VJ} = 25°C T_{VJ} = -40°C			1.5 1.6	V V
I_{GT}	V_D = 6 V; T_{VJ} = 25°C T_{VJ} = -40°C			300 400	mA mA
V_{GD} I_{GD}	T_{VJ} = 125°C; $V_D = {}^2/_3 V_{DRM}$ T_{VJ} = 125°C; $V_D = {}^2/_3 V_{DRM}$			0.2 10	V mA
I_L	T_{VJ} = 25°C; t_P = 10 µs I_G = 0.5 A; di_G/dt = 0.5 A/µs			450	mA
I_H	T_{VJ} = 25°C; V_D = 6 V; R_{GK} = ∞			200	mA
t_{gd}	T_{VJ} = 25°C; V_D = ½ V_{DRM} I_G = 0.5 A; di_G/dt = 0.5 A/µs			2	µs
R_{thJC} R_{thJH}	per Thyristor; DC per Thyristor; DC; typ.		 0,35	0.25	K/W K/W
d_S d_A a	Creeping distance on surface Creeping distance in air Max. allowable acceleration			11.2 5.0 50	mm mm m/s²

Dimensions in mm (1 mm = 0.3937")



© 2003 IXYS All rights reserved