



## AS01308MR-R 13mm Speaker

3541 Stop Eight Road • Dayton, Ohio 45414

## **Product Overview**

- 13mm diameter speaker with Neodymium magnet for 86 dB sensitivity
- 0.2W continuous, 0.4W maximum power handling and  $8\Omega$  impedance
- Mylar cone with pleated surround for wide frequency response

















## AS01308MR-R 13mm Speaker

Mechanical and Environment Testing			
Test Description	Test Condition		
High Temperature	55°C with random humidity for 96 hours		
Low Temperature	-20°C with random humidity for 96 hours		
Humidity	40°C with 90% to 95% relative humidity for 96 hours		
Vibration	1.5 mm movement modulated at 10 to 55 Hz for 2 hours		
Drop Test	75 cm free fall onto 40 mm thick board, 10 cycles		
Temperature Cycle Test	-20°C to 55°C, 5 cycles (refer to Temperature Cycle Test Graph)		

After tests, speaker shall rest for 1 hours. SPL shall not deviate ±3 dB from pre-test measurement.









SPECIFICATIONS				
PARAMETERS	VALUES	UNITS		
RATED INPUT POWER	0.2	W		
MAX INPUT POWER	0.4	W		
IMPEDANCE	8 ± 15%	OHM		
OUTPUT SPL @ 0.2W/0.1M	86 + 3	dBA		
(AT 1.5, 2.0, 2.5, 3.0 kHz)	00 ± 3	UDA		
DISTORTION (MAX.)	10%	-		
RESONANT FREQUENCY	1,050 ± 20%	Hz		
FREQUENCY RANGE	1,050 ~ 20,000	Hz		
HOUSING MATERIAL	METAL	-		
CONE MATERIAL	MYLAR	-		
MAGNET MATERIAL	Nd-Fe-B	-		
OPERATING TEMPERATURE	-20 ~ +55	°C		
WEIGHT	0.7	grams		

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

©2003, Projects Unlimited Inc.

REVISION HISTORY				
LTR	DESCRIPTION	DATE	APPROVED	
-	RELEASED FROM ENGINEERING	8/4/2005		
Α	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	10/30/2008	B.R.	
В	REVISED TOLERANCES AND ROHS STATUS	10/9/2013	M.L.	







## NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2011/65/EU COMPLIANT.

JNLESS OTHERWISE		Designed by	Date	Che	cked by
SPECIFIED: DIMENSIONS ARE IN	SIZE	J.A.F.	8/4/2005	Е	3.R.
MILLIMETERS,		M	<b>~</b>		
TOLERANCES ARE ±0.5 AND	A3		pul.		
ANGLES ARE ±3°.	, (0		<b>ALIM</b> C	Ň	
AS01308MR-R.idw		400	a projects unlimited co	mpany	

8/4/2005	E.P.	8/4/20	05   10	10/30/2008		
AS01308MR-R						
Spea	aker		Edition -	Sheet 1 / 1		

Date

Drawn Date

Approved by

AS01308MR-R.idw