

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[3M](#)  
[465XL](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# 3M

## Extended Liner Tapes

450EK • 450XL • 465XL • 466XL

476XL • 920XL • 9925XL

Technical Data

September, 2008

**Product Description** 3M™ Extended Liner Tapes have a liner that extends beyond the width of the adhesive to provide easy liner starting and removal. The liners, with the exception of 3M™ Extended Liner Tape 450EK is printed with the message, “Remove to Expose Adhesive”

### Features

- The extended liner provides a dry edge on each side of the tape for easy liner removal. Stated product widths include the dry edge of the liner.
- 3M™ Extended Liner Tapes 465XL, 920XL and 9925XL are ideal for adhesion to paper materials but also work well on many other surfaces. Some application ideas are:
  - Pressure-sensitive edges for posters and point of purchase sales advertising.
  - Permanent mounting of novelty items, note pads, literature, posters and labels.
  - Pressure-sensitive edging on business forms.
- 3M™ Extended Liner Tapes 450EK, 450XL, 465XL and 920XL are ideal for pharmaceutical outsert attachment. 3M tape 450XL has a heavier liner than 3M tape 920XL to help reduce liner breakage during application. 3M tape 450EK has the most tear resistant liner of these products. This release liner has stretch built into the paper making it tough and tear resistant. 3M tape 465XL is .002 in. thick for surface which requires more adhesive mass.
- 3M™ Extended Liner Tape 466XL is well suited to many coated, uncoated and synthetic paper applications as well as for high and low surface energy plastic film applications.
- 3M™ Extended Liner Tape 476XL is a double coated tape with a film carrier and has excellent quick stick for sealing many boxes and tubes used for various types of shipments.
- 3M™ Extended Liner Tape 9925XL is a double coated tape with a thin tissue carrier for permanent paper to paper bonding.

# 3M™ Extended Liner Tapes

450EK • 450XL • 465XL • 466XL • 476XL • 920XL • 9925XL

Construction	3M™ Extended Liner Tape 450EK	3M™ Extended Liner Tape 450XL	3M™ Extended Liner Tape 465XL	3M™ Extended Liner Tape 466XL	3M™ Extended Liner Tape 476XL	3M™ Extended Liner Tape 920XL	3M™ Extended Liner Tape 9925XL
Products	3M™ Extended Liner Tape 450EK	3M™ Extended Liner Tape 450XL	3M™ Extended Liner Tape 465XL	3M™ Extended Liner Tape 466XL	3M™ Extended Liner Tape 476XL	3M™ Extended Liner Tape 920XL	3M™ Extended Liner Tape 9925XL
Adhesive Type:*	400 Acrylic	400 Acrylic	400 Acrylic	340 Acrylic	760 Rubber	400 Acrylic	770 Rubber
Adhesive Carrier:	None	None	None	None	Polypropylene film	None	Tissue
Release Liner:	70# White Extensible Kraft	60# Kraft Glassine-Tan Green Printing	60# Densified Kraft Tan Paper Green Printing	62# Densified Kraft Off-White Paper Black Printing	43# Densified Kraft White Paper Red Printing	43# Densified Kraft White Paper Red Printing	43# Densified Kraft White Paper Black Printing
Approximate Thickness: Release Liner	0.0056 in. (0.146 mm)	0.0035 in. (0.09 mm)	0.0035 in. (0.09 mm)	0.004 in. (0.11 mm)	0.003 in. (0.08 mm)	0.0025 in. (0.065 mm)	0.002 in. (0.05 mm)
Tape Only	0.001 in. (0.025 mm) Adhesive Transfer Tape	0.001 in. (0.025 mm) Adhesive Transfer Tape	0.002 in. (0.05 mm) Adhesive Transfer Tape	0.002 in. (0.05 mm) Adhesive Transfer Tape	0.006 in. (0.16 mm) Double Coated Film Tape	0.001 in. (0.025 mm) Adhesive Transfer Tape	0.0025 in. (0.065 mm) Tissue Reinforced Double Coated Tape
Tape Color:	Clear	Clear	Clear	Clear	Clear	Clear	Off-White Translucent

\*3M™ Adhesive 340 is a medium firm acrylic pressure-sensitive adhesive system. It features very high tack to a variety of surfaces.

3M™ Adhesive 400 is a medium-firm acrylic pressure-sensitive adhesive system. It features high initial adhesion to a wide variety of materials and good shear holding power.

3M™ Adhesive 760 is a high tack synthetic rubber adhesive. It provides excellent quick stick or initial adhesion.

3M™ Adhesive 770 is a soft rubber-resin pressure sensitive adhesive system. It features high initial adhesion to a wide variety of materials.



## 3M™ Extended Liner Tapes

450EK • 450XL • 465XL • 466XL • 476XL • 920XL • 9925XL

### Application Techniques

- Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure helps develop better adhesive contact and improve bond strength.
- To obtain optimum adhesion, the bonding surfaces must be clean, dry, and well unified. Some typical surface cleaning solvents are isopropyl alcohol and heptane.\*
- Ideal tape application temperature range is 70°F to 100°F (21°C to 38°C). Initial tape application to surfaces at temperatures below 50°F (10°C) is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

**\*Note:** When using solvents, extinguish all ignition sources, including pilot lights, and follow the manufacturer's precautions and directions for use.

### Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

### Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

### Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



### Industrial Adhesives and Tapes Division Converter Markets

3M Center, Building 21-1W-10, 900 Bush Avenue  
St. Paul, MN 55144-1000  
800-223-7427 • 651-778-4244 (fax)  
www.3M.com/converter



Recycled Paper  
40% pre-consumer  
10% post-consumer

3M is a trademark of 3M Company.  
Printed in U.S.A.  
©3M 2008 70-0709-3843-9 (9/08)