### **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

3M 46-TRANSLUCENT-1

For any questions, you can email us directly: <a href="mailto:sales@integrated-circuit.com">sales@integrated-circuit.com</a>



## **3M**

# **46 Electrical Tape**

## Polyester Film/Glass Filaments, Reinforced Backing with Thermosetting Rubber, Pressure Sensitive Adhesive

**Data Sheet** 

**Properties** 

High tensile strength High dielectric strength UL recognized Class B (130°C)

3M<sup>™</sup> 46 Electrical Tape is a polyester film/glass filament tape coated with a thermosetting, pressure-sensitive rubber adhesive system. The polyester film/glass backing has excellent physical and electrical characteristics. 46 tape is especially suited for such applications as lead anchoring and banding of coils where high edge-tear resistance and low stretch under application tension are needed.

# Caliper¹ 7.0 mils (.177 mm) Breaking Strength¹ 275 lbs./in (481 N/10 mm) Elongation 5% Adhesion to Steel¹ 50 oz/in (5.4 N/10 mm) Dielectric Strength¹ 5500V Insulation Resistance¹ 3x10³ megohms

Typical Values\*

\*All values are averages based on several determinations and not intended for specification purposes. Product specifications will be provided upon request.

1.0 ratio

Test methods: 1 ASTM D-1000

Electrolytic Corrosion Factor<sup>2</sup>

<sup>&</sup>lt;sup>2</sup> 3M Test Method - available upon request



#### **Distributor of 3M: Excellent Integrated System Limited**

Datasheet of 46-TRANSLUCENT-1 - TAPE ELECTRICAL FILAMENT 1"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

3M is a trademark of 3M

#### **Important Notice**

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained herein are made in lieu of all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS THAT WERE DEFECTIVE.



**Electrical Products Division** 6801 River Place Blvd.

Austin, TX 78726-9000 800 676 8381 http://www.3m.com/elpd

© 3M 1998 78-8124-4867-4(A)