

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)  
[AKSPT/G-BLACK](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

1	2	3	4	5	6	7																																																															
A																																																																					
B																																																																					
C																																																																					
D	<p style="text-align: center;">AKSPT/x - x</p> <p>Color:            GREY - Grey            RED - Red            BLUE - Blue            BLACK - Black</p> <p>Contact Area Plating: ④            G: Gold Flash            Z: Tinned</p>																																																																				
E																																																																					
F																																																																					
G	<p style="text-align: center;"><b>ROHS compliant</b></p> <p style="text-align: center;">Unit:mm</p>																																																																				
H	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Scale</th> <th>Free</th> <th></th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td colspan="7"><b>TOLERANCE</b></td> </tr> <tr> <td>.X</td> <td>±0.38</td> <td>④</td> <td>Update</td> <td>07.06.2013</td> <td>Winnie</td> <td>Drawn</td> </tr> <tr> <td>.XX</td> <td>±0.25</td> <td>④</td> <td>Update</td> <td>29.10.1995</td> <td>Hellwig</td> <td>Approved</td> </tr> <tr> <td>.XXX</td> <td>±0.13</td> <td>③</td> <td>Update the material of contact</td> <td>07.06.2013</td> <td>Winnie</td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>②</td> <td>Update</td> <td>15.10.2012</td> <td>Army</td> <td></td> </tr> <tr> <td>X.°</td> <td>±1°</td> <td>②</td> <td>Update</td> <td>27.07.2009</td> <td>Rale</td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>①</td> <td>Drawn</td> <td>29.10.1995</td> <td>Hellwig</td> <td></td> </tr> <tr> <td>UNIT</td> <td>mm</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> </tr> </tbody> </table>						Scale	Free						<b>TOLERANCE</b>							.X	±0.38	④	Update	07.06.2013	Winnie	Drawn	.XX	±0.25	④	Update	29.10.1995	Hellwig	Approved	.XXX	±0.13	③	Update the material of contact	07.06.2013	Winnie		DIM	TOL	②	Update	15.10.2012	Army		X.°	±1°	②	Update	27.07.2009	Rale		Angle	TOL	①	Drawn	29.10.1995	Hellwig		UNIT	mm	Id.	Modification	Date	Name	
Scale	Free																																																																				
<b>TOLERANCE</b>																																																																					
.X	±0.38	④	Update	07.06.2013	Winnie	Drawn																																																															
.XX	±0.25	④	Update	29.10.1995	Hellwig	Approved																																																															
.XXX	±0.13	③	Update the material of contact	07.06.2013	Winnie																																																																
DIM	TOL	②	Update	15.10.2012	Army																																																																
X.°	±1°	②	Update	27.07.2009	Rale																																																																
Angle	TOL	①	Drawn	29.10.1995	Hellwig																																																																
UNIT	mm	Id.	Modification	Date	Name																																																																
1	2	3	4	5	6	7																																																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Customer-No.</th> <th>Date</th> <th>Name</th> <th>Customer-No.</th> <th>ASSMANN WSW-No.</th> <th>Drawing-No.</th> <th>Replace</th> </tr> </thead> <tbody> <tr> <td></td> <td>29.10.1995</td> <td>Hellwig</td> <td></td> <td>AKSPT/x-x</td> <td>ASS 0336 CO</td> <td>rev04</td> </tr> </tbody> </table>							Customer-No.	Date	Name	Customer-No.	ASSMANN WSW-No.	Drawing-No.	Replace		29.10.1995	Hellwig		AKSPT/x-x	ASS 0336 CO	rev04																																																	
Customer-No.	Date	Name	Customer-No.	ASSMANN WSW-No.	Drawing-No.	Replace																																																															
	29.10.1995	Hellwig		AKSPT/x-x	ASS 0336 CO	rev04																																																															
<p style="text-align: center;"><b>ASSMANN</b>  <small>W S W / components</small></p>																																																																					
<p style="text-align: center;">SHEET</p>																																																																					

**NOTES:**

1. Insulation: 30% Glass Filled PBT, UL94V-0
- ② 2.Contact : Brass
3. Current Rating: 3A Max
4. Dielectric Voltage: 1000V rms / 1 minute
5. Insulation Resistance: 1000M ohm Min.
6. Contact Resistance: 30m ohm Max.
7. Operating and Storage Temperature: -40°C ~ +105°C
- ④ 8. Mating Cycles: 10 Min.