

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[AKSG-200/G](#)

For any questions, you can email us directly:

sales@integrated-circuit.com


RoHS COMPLIANT

REVISIONS				
REV	ECN NO.	DESCRIPTION	APPROVED BY	DATE
A			ELTON MENG	2006-05-22

Product Specification

Material
 Insulator :Glass-Filled Thermoplastic
 PBT,UL94V-0 rates
Contact :Brass
 Plated full gold or selected gold in mating area, 100µ min. tin-lead on termination area, with entire contact under-plated 50µ min. Nickel


Electrical
 Contact Resistance :30 milliohms
 Max at 1 AMP DC.
 Insulation Resistance :1000 megohms at 500 VDC
 Dielectric Withstanding Voltage :
 500 VAC/rms 60Hz for 1 minute
 Current Rating :1 AMP
 Voltage Rating :250 VAC/rms 60Hz



A Type

AKSG-200-X-R

Contact Plating
G Gold Contact
Z Tinned



B Type

AKSO-200-X-R

Contact Plating
G Gold Contact
Z Tinned



DO NOT SCALE DRAWING

DIMENSIONS: <input type="checkbox"/> MM (INCH) <input type="checkbox"/> INCH (MM) <input checked="" type="checkbox"/> MM ONLY		CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE DRAWN BY AND DATE: JUSTIN XING 03-07-06 CHECKED BY AND DATE: JUSTIN XING 03-07-06 APPROVED BY AND DATE: ELTON MENG 06-09-06 THIRD ANGLE PROJECTION
UNLESS OTHERWISE SPECIFIED, GENERAL TOLERANCE: DECIMALS X: ±0.38 (0.015) X*: ±3* .X ±0.25 (0.010) .X*: ±1.0* .XX ±0.13 (0.005)		
MATERIAL:		TITLE: MINI JUMPER 2.00MM (0.079")
FINISH:		
SCALE: 5 : 1		SIZE: A3

ASSMANN
Electronics, Inc.

FILE NO:	REV A
SHEET 1 OF 1	