

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Murata Power Solutions Inc.](#)
[45102C](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



FEATURES


- RoHS compliant
- 0.28μH to 1.0mH
- Up to 8A I_{DC}
- Bobbin format
- Surface mount
- Integral EMI shield
- Compact size
- Tape and reel packaging
- UL 94V-0 materials
- J-STD-020-C reflow

DESCRIPTION

The 4500 series is a lower profile version of our 4600 series range of bobbin-wound, shielded inductors. They are suitable for power-line filtering found in consumer electronics such as desktop computers, LED applications and GPS systems, as well as in a vast range of industrial and telecom applications including network hubs, bridges & routers, and high frequency wireless communication devices.

These surface mount inductors are extremely compact and have an integral shield, making them useful in EMI sensitive applications.

PIN CONNECTIONS (TOP VIEW)



For full details go to
www.murata-ps.com/rohs


4500 Series

Shielded Surface Mount Power Inductors


SELECTION GUIDE

Order Code	Inductance (10kHz, 0.1V _{AC})	DC Current ¹		DC Resistance	
	±20%				
	Nom. μH	Max. A		Max. mΩ	
45281C	0.28 (±30%)	8.0		9	
45541C	0.54 (±30%)	7.0		11	
45102C	1.0 (±30%)	6.0		14	
45152C	1.5 (±30%)	5.5		17	
45222C	2.2 (±30%)	4.5		26	
45332C	3.3 (±30%)	3.7		34	
45472C	4.7 (±30%)	3.2		47	
45682C	6.8 (±30%)	2.6		66	
45103C	10	2.2		82	
45153C	15	1.8		120	
45223C	22	1.35		180	
45333C	33	1.25		250	
45473C	47	1.05		360	
45683C	68	0.82		510	
45104C	100	0.70		710	
45154C	150	0.58		1000	
45224C	220	0.50		1550	
45334C	330	0.35		2540	
45474C	470	0.32		3250	
45684C	680	0.26		5000	
45105C	1000	0.23		6500	

MECHANICAL DIMENSIONS



Recommended Footprint Details*



*Distance between the outside ends of the terminations is 7.1±0.1 (0.28±0.004)
Unless otherwise stated, all dimensions in mm (inches) ± 0.25 (0.010).
Package weight: 0.64g Typ.

ABSOLUTE MAXIMUM RATINGS

Operating temperature range	-40°C to 125°C
Storage temperature range	-40°C to 150°C

SOLDERING INFORMATION²


Peak reflow solder temperature	250°C
Pin finish	Tin

Specifications typical at T_a = 25°C


1 Maximum DC current occurs when either the inductance falls to 75% of its nominal value or when its temperature rise reaches 40°C, whichever is sooner.

2 For further information, please visit www.murata-ps.com/rohs


INDUCTANCE Vs CURRENT



TEMPERATURE Vs CURRENT




INDUCTANCE Vs FREQUENCY




TAPE & REEL SPECIFICATIONS

REEL OUTLINE DIMENSIONS



TAPE OUTLINE DIMENSIONS



Murata Power Solutions, Inc.
11 Cabot Boulevard, Mansfield, MA 02048-1151 U.S.A.
ISO 9001 and 14001 REGISTERED

Murata Power Solutions, Inc. makes no representation that the use of its products in the circuits described herein, or the use of other technical information contained herein, will not infringe upon existing or future patent rights. The descriptions contained herein do not imply the granting of licenses to make, use, or sell equipment constructed in accordance therewith. Specifications are subject to change without notice.

© 2011 Murata Power Solutions, Inc.