

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Chemtronics](#)  
[CW7270](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# CHEMTRONICS

## Technical Data Sheet

**CW7270**

### CircuitWorks<sup>®</sup> Silicone Free Heat Sink Grease

#### PRODUCT DESCRIPTION

CircuitWorks<sup>®</sup> Silicone Free Heat Sink Grease facilitates heat transfer away from electrical/electronic components and into heat sinks. This silicone-free compound shows no creep or migration over a wide temperature range. Thickened with a proprietary thermally conductive zinc oxide ceramic, the CircuitWorks<sup>®</sup> Silicone Free Heat Sink Grease creates an effective heat sink interface in electrical/electronic equipment.


- Exceeds MIL-C-47113 for thermal conductivity
- Noncorrosive
- High dielectric strength
- Low migration
- Stable from -15°C to 200°C
- Nonflammable

#### TYPICAL APPLICATIONS

CircuitWorks<sup>®</sup> Silicone Free Heat Sink Grease may be used for electronics applications including:

- Effective Thermal Coupler for any Heat Sink Device
- Nonflammable Protective Coating
- High Voltage Corona Protection
- Excellent for Improving Readings on Contact Type Thermocouples
- Ideal for Silicone Sensitive Environments

#### TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

<b>Color</b>	White
<b>Specific Gravity @ 25°C (77°F)</b>	2.4
<b>Usable Temperature Range</b>	5°F (-15°C) to 392°F (200°C)
<b>Dielectric Strength, volts/mil</b>	500
<b>Dielectric Constant @ 100 Hz</b>	4.4
<b>Dissipation Factor @ 100 Hz</b>	0.005
<b>Volume Resistivity, ohm-cm</b>	1 x 10 <sup>14</sup>
<b>Arc Resistance, seconds</b>	120
<b>Thermal Conductivity, Cal-cm/sec-cm<sup>2</sup> -°C</b>	1.7 x 10 <sup>-3</sup>
<b>BTU-in/hr-ft<sup>2</sup> -°F</b>	4.92
<b>W/m<sup>2</sup>K</b>	0.71
<b>Shelflife</b>	5 years
<b>RoHS Compliant</b>	

#### COMPATIBILITY

CircuitWorks<sup>®</sup> Silicone Free Heat Sink Grease is generally compatible with most materials used in printed circuit board fabrication.

Material	Compatibility
Ceramic	Good
Clean Metals	Good
Glass	Good
Silicone Resins	Good
Painted Surfaces	Good
Plastic Surfaces	Good
Vulcanized Silicone Rubber	Good

## USAGE INSTRUCTIONS

For industrial use only.

Read MSDS carefully prior to use.

### Application:

Apply CircuitWorks® Silicone Free Heat Sink Grease directly to surface or use the application tip. Remove cap from syringe and gently depress the plunger. Spread the material in a thin layer on all mounting and threaded surfaces of the device and the chassis.

**Clean-Up:** Wipe away excess material using a Chemtronics® ControlWipes™ and thoroughly clean the surface using Chemtronics® Electro-Wash® PX.

## TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.**

## AVAILABILITY

**CW7270** 8 gm / 0.28 oz syringe

### ENVIRONMENTAL IMPACT DATA

ODP	None	VOC	None
HCFC	None	HFC	None

Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990. Hydrochlorofluorocarbons (HCFCs) are regulated under the Montreal Protocol as Class II ozone depleting substances. Volatile Organic Compound (VOC) information is calculated on a weight basis using the VOC definition of California Air Resources Board (CARB) Consumer Product Regulations, South Coast Air Quality Management District (SCAQMD) Rule 102 and the Federal definition published in 40 CFR 51.100(s). Hydrofluorocarbons (HFCs) are not currently regulated.

### NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

## CHEMTRONICS

8125 COBB CENTER DRIVE

KENNESAW, GA 30152

1-770-424-4888

REV. C (08/13)

Chemtronics®, Electro-Wash® and CircuitWorks® are registered trademarks of Chemtronics. All rights reserved. ControlWipes™ is a trademark of Chemtronics. All rights reserved.

### DISTRIBUTED BY: