

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Honeywell Sensing and Productivity Solutions](#)
[3100U 00031439](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Honeywell Sensing and Control



Home > Products > Thermostats > 3100U > Product Page

3100U 00031439

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback



Actual product appearance may vary.

3100 Series Hermetic Thermostats

Features

Hermetically sealed
 Tight tolerances
 Tight differentials

Potential Applications

Computers
 Medical electronics
 Power supplies
 Industrial controls
 Test equipment
 Infotech

Description

The 3100 Series consists of a single pole, single throw switch activated by a snap-action bimetal disc. Temperature calibrations are pre-set at the factory and each unit is 100% thermally and mechanically inspected. It is available to open or close on temperature rise. The case is laser welded to form a hermetically-sealed steel housing with a glass-to-metal seal at the terminal junction. It is manufactured and tested to meet or exceed critical commercial and industrial specifications.

Supporting Documentation

None Available

| Product Specifications | |
|------------------------------|---|
| Functional Properties | Open on rise |
| Reset Type | Automatic |
| Amperage | 3 A resistive max. |
| Voltage | 120 Vac |
| Operating Temperature | -29 °C to 260 °C [-20 °F to 500 °F] |
| Environmental Exposure Range | -62 °C to 288 °C [-80 °F to 550 °F] |
| Open Temperature | 48.9 °C [120 °F] |
| Close Temperature | 37.8 °C [100 °F] |
| Open Tolerance | 2.8 °C [5 °F] |
| Close Tolerance | 2.8 °C [5 °F] |
| Dielectric Strength | MIL-STD-202, Method 301; 1250 Vac 60 Hz - Terminal to Case |
| Insulation Resistance | MIL-STD-202, Method 302; 50 MOhm |

My Links

- Login to iCOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

Keyword Search

Search for product and support information.

Product Search

Part number search:

Use (*) to expand search

→ Specification Search



| | |
|--------------------------------|---|
| Contact Resistance | MIL-STD-202, Method 307; 0.050 Ohm max. |
| Hermetic Seal | MIL-STD-202, Method 112; Cond. 1x10 ⁻⁵ |
| Moisture Resistance | MIL-STD-202, Method 106 |
| Housing Material | Steel housing hermetically sealed with glass-to-metal seal at terminal junction |
| Contact Material | Silver |
| Agency Approvals and Standards | UL |
| Mounting | B209 fixed bracket |
| Series Name | 3100U |

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)