

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Mallory Sonalert Products](#)  
[SC628NP](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

<b>MALLORY</b> Mallory Sonalert Products Inc.	Part # <b>SC628NP</b>
	Revision <b>D</b>

**Specifications:**

Sound level Category	Loud Sound Level
Mode of Operation	Fast Pulse
Mounting	Panel (see note B)
Voltage Rating	6 to 28 VDC
Frequency	2900 Hz ±500 Hz
Loudness (Min. Voltage)	80 dB(A) min. @ 2 FT and 6 VDC
Loudness (Max Voltage)	90 dB(A) min. @ 2 FT and 28 VDC
Current Draw	4 mA Max @ 6 VDC
Current Draw	16 mA Max @ 28 V/DC
Min. Pulse Rate (PPS)	2 @ 6 VDC
Max. Pulse Rate (PPS)	10 @ 28 VDC
Duty Cycle (%)	50 Approx.
Storage Temperature	-40°C to +85°C
Operating Temperature	-30°C to +65°C
Weight (Typical)	1.6 oz (45 g)
Housing	6/6 Nylon, Color Black
Options	For other options contact factory

**Dimensions:** Inches (mm):

PART DIMENSIONS BEFORE CODE DATE 0811 5

PART DIMENSIONS AFTER CODE DATE 0812 1

