

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Wiha](#)
[20006](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Wiha Quality Tools
See Product Category Index

[Go To Image Index](#)

[Go To Numerical Index](#)

96

Toll Free: (800) 494-6104



1000Volt

NEW
From Wiha

[SHOP](#)



1000Volt

[SHOP](#)

200 91 Set 15 Pcs. Metric Open End Insulated Spanners

Item No.	Ø _{MM} mm	OAL mm	Ø _{MM} mm	OAL mm	lbs.
200 91	200 06	6	97	200 14	14 150 3.0
	200 07	7	98	200 15	15 151
	200 08	8	104	200 16	16 164
	200 09	9	108	200 17	17 162
	200 10	10	107	200 19	19 178
	200 11	11	118	200 22	22 196
	200 12	12	129	200 24	24 211
	200 13	13	137		



1000Volt

[SHOP](#)

200 93 Set 8 Pcs. Metric Open End Insulated Spanners

Item No.	Ø _{MM} mm	OAL mm	Ø _{MM} mm	OAL mm	lbs.
200 93	200 06	6	97	200 13	13 137 1.4
	200 07	7	98	200 14	14 150
	200 08	8	104	200 17	17 162
	200 10	10	107	200 19	19 178

Use & Care Guide For Insulated Tools:

Store tools to minimize risk of damage to insulation, always wear approved eye protection, inspect insulation prior to each use of any insulated tool. Use insulated tools where the ambient temperature is between -20 to +70° C. Have a qualified safety technician visually inspect insulation on tools annually for safe use.

WARNING!

Insulated Tools are intended to provide protection against accidental contact with charged energized circuits. For maximum safety we recommend de-energizing all circuits whenever possible before starting work on electrical apparatus or conductors. Always visually inspect insulation on tools before use, do not use tools if insulation shows signs of wear or damage to the insulated areas of the tool. Wear appropriate eye protection when using hand tools. Use NFPA70E certified insulated protective outer wear when appropriate.

[PREVIOUS](#)

[NEXT](#)

INDEX

200 Metric Open-Ended Spanners, With Insulated Handle
Insulation According to VDE Specification 0680 and EN/IEC 60900, DIN 7446, up to 1000 Volt. Individually Tested. Chrome-vanadium steel, hardened. Angled 15°.

Item No.	Ø _{MM} mm	OAL mm	OAL Inch	lbs.	pkg.
200 06	6	97	3.8	.04	1
200 07	7	98	3.9	.05	1
200 08	8	104	4.1	.07	1
200 09	9	108	4.3	.07	1
200 10	10	107	4.2	.08	1
200 11	11	118	4.6	.11	1
200 12	12	129	5.1	.11	1
200 13	13	137	5.4	.17	1
200 14	14	150	5.9	.19	1
200 15	15	151	5.9	.17	1
200 16	16	164	6.5	.22	1
200 17	17	162	6.4	.24	1
200 18	18	173	6.8	.33	1
200 19	19	178	7.0	.32	1
200 22	22	196	7.7	.39	1
200 24	24	211	8.3	.58	1
200 27	27	218	8.6	.60	1
200 30	30	235	9.3	.90	1
200 32	32	237	9.3	.93	1