

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Integrated Device Technology \(IDT\)](#)  
[952801CFLFT](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Home > Products > > 952801 > 952801CFLFT

[Add to myIDT \[?\]](#)

You may also like...

## 952801CFLFT

### Category:

Generic Part: 952801

Market Group: PC CLOCK

Description: PC MAIN CLOCK

The ICS952801 is a two chip clock solution for desktop designs using SIS 755/760 style chipsets. When used with a zero delay buffer such as the ICS9179-16 for PC133 or the ICS93735 for DDR applications it provides all the necessary clocks signals for such a system. Output Features: 2 - Pairs of differential push-pull K8CPU outputs @ 8 - PCICLK @ 3.3V @ 2 - AGPCLK @ 3.3V @ 3 - REF @ 3.3V @ 2 - ZCLK @ 3.3V @ 1 - 24\_48MHz @ 3.3V @ 1 - 48MHz @ 3.3V



### Parameters

|                         |                |
|-------------------------|----------------|
| Package                 | SSOP48 (PVG48) |
| Speed                   | NA             |
| Temperature             | C              |
| Voltage                 | 3.3 V          |
| Status                  | Active         |
| Sample                  | No             |
| Minimum Order Quantity  | 1000           |
| Factory Order Increment | 1000           |

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

| Type | Title                  | Size  | Revision Date |
|------|------------------------|-------|---------------|
| Misc | PC Clocks Contact Info | 61 KB | 05/29/2007    |

### Package

|                                  |                          |
|----------------------------------|--------------------------|
| Description                      | SSOP 300 ML, 48LD        |
| Class                            | PLASTIC                  |
| Moisture Sensitivity Level (MSL) | 1                        |
| Category                         | Green                    |
| Moisture Exposure Floor Life     | Unlimited @ <30°C/85% RH |
| Peak Reflow Temperature          | 260°C                    |
| Rebake Conditions                | N/A                      |
| Length                           | 15.9                     |
| Mark                             | PVG                      |
| Width                            | 7.5                      |
| Pitch                            | 0.64                     |
| Thickness                        | 2.3                      |
| Status                           | Active                   |