

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Integrated Device Technology \(IDT\)](#)
[ICS952911BFT](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Home > Products > > 952911 > 952911BFT

[Add to myIDT \[?\]](#)

You may also like...

952911BFT

Category:

Generic Part: 952911

Market Group: PC CLOCK

Description: PC MAIN CLOCK

ICS952911 is a 48 pin clock chip for VIAPT890 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system. Output Features: $\hat{\epsilon}$ 2 - 0.7V current-mode differential CPU pairs $\hat{\epsilon}$ 10 - PCI, 3 free running, 33MHz $\hat{\epsilon}$ 3 - REF, 14.318MHz $\hat{\epsilon}$ 3 - 3V66, 66.66MHz $\hat{\epsilon}$ 1 - 48MHz $\hat{\epsilon}$ 1 - 24/48MHz $\hat{\epsilon}$ 2 - 25MHz @ 2.5V



Parameters

Package	SSOP 48 (PV48)
Speed	NA
Temperature	C
Voltage	3.3 V
Status	Active
Sample	No
Minimum Order Quantity	1000
Factory Order Increment	1000

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SSOP 300 ML, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	225°C
Rebake Conditions	N/A
Length	15.9
Mark	F
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active