

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Integrated Device Technology \(IDT\)](#)

[ICS9LPRS355CGLF](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



English | 简体中文 | 日本語

Search Entire Site [GO](#)

[Contact IDT](#) | [Investors](#) | [Press](#)

[About IDT](#)

[Products](#)

[Applications](#)

[Support](#)

[myIDT](#)

[Document Search](#) | [Package Search](#) | [Parametric Search](#) | [Cross Reference Search](#) | [Green & RoHS](#) | [Calculators](#) | [Thermal Data](#) | [Reliability & Quality](#) | [Military](#)

[Home](#) > [Products](#) > [Clock / Timing Devices](#) > [PC-Notebook-Server Clocks](#) > [Clock Synthesizer by Chipset Vendor](#) > [Notebook Chipsets](#) > [9LPRS355](#) > [9LPRS355CGLF](#)

[Add to myIDT \[?\]](#)

You may also like...

9LPRS355CGLF

Category: Notebook Chipsets

Generic Part: 9LPRS355

Market Group: PC CLOCK

Description: CK505 COMPLIANT CLOCK
 ICS9LPRS355 follows Intel CK505 Yellow Cover specification. This clock synthesizer provides a single chip solution for next generation P4 Intel processors and Intel chipsets. ICS9LPRS355 is driven with a 14.318MHz crystal. It also provides a tight ppm accuracy output for Serial ATA and PCI-Express support.

Output Features:

- 2 - CPU differential low power push-pull pairs
- 9 - SRC differential low power push-pull pairs
- 1 - CPU/SRC selectable differential low power push-pull pair
- 1 - SRC/DOT selectable differential low power push-pull pair
- 5 - PCI, 33MHz
- 1 - PCI_F, 33MHz free running
- 1 - USB, 48MHz
- 1 - REF, 14.318MHz

Time is money

Parameters

Package	TSSOP 64 (PAG64)
Voltage	3.3 V
Package	TSSOP 64
Speed	NA
Temperature	C
Status	Active
Sample	Yes
Minimum Order Quantity	140
Factory Order Increment	28

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Type	Title	Size	Revision Date
Datasheet	954201 Datasheet	163 KB	03/27/2006
	954204 Datasheet	200 KB	03/27/2006
	954321 Datasheet	225 KB	03/27/2006
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	TSSOP 6.10 MM
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	260°C
Rebake Conditions	N/A
Length	17.0
Mark	G
Width	6.1
Pitch	0.5
Thickness	1.0
Status	Active