

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Integrated Device Technology \(IDT\)](#)  
[IDT76T1200BH](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



English | 简体中文 | 日本語

Search Entire Site

Contact IDT | Investors | Press

About IDT

Products

Applications

Support

myIDT

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > Search Engines > Content Inspection Engines > PAX.port Content Inspection Engines > 76T1200 > 76T1200BH

Add to myIDT [?]

You may also like...

## 76T1200BH

**Category:** PAX.port Content Inspection Engines  
**Generic Part:** 76T1200  
**Market Group:** IP-CO  
**Description:** 2.5V PAX PORT  
 4-Channel, multi-gigabit optimized for Layer 7 content inspection and classification

**Time is money**

### Parameters

Package	PBGA 481 (BH481)
Speed	NA
Temperature	C
Voltage	2.5 V
Status	New
Sample	Yes
Minimum Order Quantity	10
Factory Order Increment	10

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Product Change Notice	PCN#: A-0310-01, Green Products	27 KB	10/10/2003
	PCN#: A-0410-02, Change IDT marking logo with new IDT gridless w	25 KB	10/08/2004
	PCN#: A-0412-04 - To comply with Pb-free labels - Green Products	81 KB	12/14/2004
	PCN#: TB-0512-01 Reel Color Changed from Blue to Black	730 KB	12/16/2005
Product Delete Notice	PDN SR0501	70 KB	01/17/2005

### Package

Description	PBGA 27.0 X 27.0 MM
Class	PLASTIC
Moisture Sensitivity Level (MSL)	3
Category	Standard
Moisture Exposure Floor Life	168 hrs. @ <30°C/60% RH
Peak Reflow Temperature	225°C
Rebake Conditions	48 hrs.@125°C
Length	27.0
Mark	BH
Width	27.0
Pitch	11.0
Thickness	1.17
Status	Active