

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Fairchild Semiconductor](#)

[H22A1](#)

For any questions, you can email us directly:


sales@integrated-circuit.com

FAIRCHILD
SEMICONDUCTOR™


SLOTTED OPTICAL SWITCH

H22A1/2/3

PACKAGE DIMENSIONS



ST1340-01




ST1340-02

SYMBOL	MILLIMETERS		INCHES		NOTES
	MIN.	MAX.	MIN.	MAX.	
A	10.7	11.0	.422	.433	
A ₁	3.0	3.2	.119	.125	
φb	.600	.750	.024	.030	2
b ₁	.50 NOM.		.020 NOM.		2
D ₁	11.6	12.0	.457	.472	
D ₂	3.0	3.3	.119	.129	
e ₁	6.9	7.5	.272	.295	
e ₂	2.3	2.8	.091	.110	
E	6.15	6.35	.243	.249	
L	8.00		.315		
S	.85	1.0	.034	.039	
S ₁	3.45	3.75	.136	.147	
T	2.6 NOM.		.103 NOM.		3

NOTES:

1. INCH DIMENSIONS ARE DERIVED FROM MILLIMETERS.
2. FOUR LEADS. LEAD CROSS SECTION IS CONTROLLED BETWEEN 1.27mm (.050") FROM SEATING PLANE AND THE END OF THE LEADS.
3. THE SENSING AREA IS DEFINED BY THE "S" DIMENSION AND BY DIMENSION "T" ±0.75mm (±.030 INCH).

PACKAGE OUTLINE



ST1609

DESCRIPTION

The H22A Slotted Optical Switch is a gallium arsenide light emitting diode coupled to a silicon photodarlington in a plastic housing. The packaging system is designed to optimize the mechanical resolution, coupling efficiency, ambient light rejection, cost and reliability. The gap in the housing provides a means of interrupting the signal with an opaque material, switching the output from an "ON" to an "OFF" state.

FEATURES

- Opaque housing
- Low cost
- .035" apertures
- High I_{C(ON)}



SLOTTED OPTICAL SWITCH

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ Unless Otherwise Specified)	
Storage Temperature	-55°C to $+100^\circ\text{C}$
Operating Temperature	-55°C to $+100^\circ\text{C}$
Soldering:	
Lead Temperature (Iron)	240°C for 5 sec. ^(3,4,5)
Lead Temperature (Flow)	260°C for 10 sec. ^(3,4)
INPUT DIODE	
Continuous Forward Current	60 mA
Reverse Voltage	6.0 Volts
Power Dissipation	100 mW ⁽¹⁾
OUTPUT TRANSISTOR	
Collector-Emitter Voltage	30 Volts
Emitter-Collector Voltage	6 Volts
Power Dissipation	150 mW ⁽²⁾

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless Otherwise Specified)						
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
INPUT DIODE						
Forward Voltage	V_F	—		1.7	V	$I_F = 60\text{ mA}$
Reverse Breakdown Voltage	V_R	6.0		—	V	$I_R = 10\mu\text{A}$
Reverse Leakage Current	I_R	—		1.0	μA	$V_R = 3\text{ V}$
OUTPUT TRANSISTOR						
Emitter-Collector Breakdown	BV_{ECO}	6.0		—	V	$I_E = 100\mu\text{A}, E_e = 0$
Collector-Emitter Breakdown	BV_{CEO}	30		—	V	$I_C = 1\text{ mA}, E_e = 0$
Collector-Emitter Leakage	I_{CEO}	—		100	nA	$V_{CE} = 25\text{ V}, E_e = 0$
COUPLED						
On-State Collector Current	$I_{C(ON)}$		See page 3.		mA	
Saturation Voltage	$V_{CE(SAT)}$		See page 3.		V	
Turn-On Time	t_{ON}		See page 3.		μS	
Turn-Off Time	t_{OFF}		See page 3.		μS	

NOTES
<ol style="list-style-type: none"> Derate power dissipation linearly 1.33 mW/$^\circ\text{C}$ above 25°C. Derate power dissipation linearly 2.00 mW/$^\circ\text{C}$ above 25°C. RMA flux is recommended. Methanol or Isopropyl alcohols are recommended as cleaning agents. Soldering iron tip $\frac{1}{16}$" (1.6 mm) from housing.




SLOTTED OPTICAL SWITCH

$I_{C(ON)}$, $V_{CE(SAT)}$, t_{on} AND t_{off}						
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
ON-STATE COLLECTOR CURRENT						
H22A1	$I_{C(ON)}$	0.15	—	—	mA	$I_F = 5mA, V_{CE} = 5V$
H22A2	$I_{C(ON)}$	0.30	—	—	mA	$I_F = 5mA, V_{CE} = 5V$
H22A3	$I_{C(ON)}$	0.60	—	—	mA	$I_F = 5mA, V_{CE} = 5V$
H22A1	$I_{C(ON)}$	1.0	—	—	mA	$I_F = 20mA, V_{CE} = 5V$
H22A2	$I_{C(ON)}$	2.0	—	—	mA	$I_F = 20mA, V_{CE} = 5V$
H22A3	$I_{C(ON)}$	4.0	—	—	mA	$I_F = 20mA, V_{CE} = 5V$
H22A1	$I_{C(ON)}$	1.9	—	—	mA	$I_F = 30mA, V_{CE} = 5V$
H22A2	$I_{C(ON)}$	3.0	—	—	mA	$I_F = 30mA, V_{CE} = 5V$
H22A3	$I_{C(ON)}$	5.5	—	—	mA	$I_F = 30mA, V_{CE} = 5V$
SATURATION VOLTAGE						
H22A2	$V_{CE(SAT)}$	—	—	0.40	V	$I_F = 20mA, I_C = 1.8mA$
H22A3	$V_{CE(SAT)}$	—	—	0.40	V	$I_F = 20mA, I_C = 1.8mA$
H22A1	$V_{CE(SAT)}$	—	—	0.40	V	$I_F = 30mA, I_C = 1.8mA$
Turn-On Time	t_{on}	—	8	—	μS	$V_{CC} = 5V, I_F = 30 mA, R_L = 2.5K\Omega$
Turn-Off Time	t_{off}	—	50	—	μS	$V_{CC} = 5V, I_F = 30 mA, R_L = 2.5K\Omega$

FAIRCHILD
SEMICONDUCTOR™

SLOTTED OPTICAL SWITCH





SLOTTED OPTICAL SWITCH

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.