

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[AK67401-2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

	1	2	3	4	5	6	7																													
A									A																											
B									B																											
C									C																											
D	<p>PIN ASSIGNMENT</p> <table border="1"> <tr> <td>P1</td> <td>RED</td> <td>P2</td> </tr> <tr> <td>1</td> <td>WHITE</td> <td>1</td> </tr> <tr> <td>2</td> <td>GREEN</td> <td>2</td> </tr> <tr> <td>3</td> <td>BLACK</td> <td>3</td> </tr> <tr> <td>5</td> <td>DRAIN + BRAID</td> <td>5</td> </tr> <tr> <td>SHELL</td> <td></td> <td>SHELL</td> </tr> </table>								P1	RED	P2	1	WHITE	1	2	GREEN	2	3	BLACK	3	5	DRAIN + BRAID	5	SHELL		SHELL	D									
P1	RED	P2																																		
1	WHITE	1																																		
2	GREEN	2																																		
3	BLACK	3																																		
5	DRAIN + BRAID	5																																		
SHELL		SHELL																																		
E	<p>Material:</p> <ul style="list-style-type: none"> Cable: USB2.0 UL2725 [28AWG(7/0.12TC+A:)*1P+ 28AWG(7/0.12TC)*2C]+AEB(488 TC) <ul style="list-style-type: none"> - Jacket: Black - OD: 3.5MM Connectors: Micro USB 5P B/M Solder Type <ul style="list-style-type: none"> - Shell: Nickel - Pin: G/F - Insulator Color: Black Outer Jacket: Black PVC-50P <p>Electrical:</p> <ul style="list-style-type: none"> 100% short, open, miswire test Conduct resistance: 2Ω Max. Insulation resistance: 5MΩ Min. Hi-Pot test: 300V DC 								E																											
F									F																											
G	<table border="1"> <tr> <td>Scale</td> <td>1:1</td> </tr> <tr> <td>TOLERANCE</td> <td></td> </tr> <tr> <td>X.X</td> <td>±0.40</td> </tr> <tr> <td>X.XX</td> <td>±0.25</td> </tr> <tr> <td>X.XXX</td> <td>±0.15</td> </tr> <tr> <td>Angle</td> <td>±3°</td> </tr> </table>		Scale	1:1	TOLERANCE		X.X	±0.40	X.XX	±0.25	X.XXX	±0.15	Angle	±3°			<table border="1"> <tr> <td>Drawn</td> <td>10/11/12</td> <td>Miller</td> </tr> <tr> <td>Approved</td> <td>10/11/12</td> <td>Warner</td> </tr> </table>		Drawn	10/11/12	Miller	Approved	10/11/12	Warner	<table border="1"> <tr> <td>Item No.</td> <td rowspan="2">AK67401-2</td> </tr> <tr> <td>Title</td> <td>USB2.0 Micro Connection Cable, 2 Meters USB B Micro Male <=> USB B Micro Male</td> </tr> <tr> <td>Drawing No.</td> <td></td> </tr> <tr> <td>Replace</td> <td>rev00</td> </tr> <tr> <td>Sheet</td> <td></td> </tr> </table>		Item No.	AK67401-2	Title	USB2.0 Micro Connection Cable, 2 Meters USB B Micro Male <=> USB B Micro Male	Drawing No.		Replace	rev00	Sheet	
Scale	1:1																																			
TOLERANCE																																				
X.X	±0.40																																			
X.XX	±0.25																																			
X.XXX	±0.15																																			
Angle	±3°																																			
Drawn	10/11/12	Miller																																		
Approved	10/11/12	Warner																																		
Item No.	AK67401-2																																			
Title		USB2.0 Micro Connection Cable, 2 Meters USB B Micro Male <=> USB B Micro Male																																		
Drawing No.																																				
Replace	rev00																																			
Sheet																																				
H																																				
	1	2	3	4	5	6	7																													