

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Laird Technologies EMI](#)

[BMI-S-205-F](#)


For any questions, you can email us directly:

sales@integrated-circuit.com

Laird Technologies
 Web site: www.LairdTech.com

All Categories > EMI Solutions > EMI Shielding & Gaskets > Board-Level Shielding > Standard Surface Mount Shields-Two-Piece > Item # BMIS-205

Item # BMIS-205 Standard Surface Mount Shields-Two-Piece



[larger image](#)

- 121 BGA
- 32, 44, 52 PLCC
- 48, 100 VQFP
- 44, 48, 64, 80, 100 QFP

Specifications

Surface Area	1.461 inches ²
Surface Area	942.50 mm ²
Maximum Overall Dimension	1.000 x 1.500 inches
Maximum Overall Dimension	25.40 x 38.10 mm
Maximum Overall Height	0.236 inches
Maximum Overall Height	6.00 mm
Material Thickness	0.20 mm
Carrier Tape Width	56 mm
Carrier Tape Pitch	44 mm
Weight	1.6 gms
Pick-up Spot Diameter	≥ 6 mm
Carrier Tape Material	LTIMS-LCB
Cover Tape Material	LTIMS-PSA
Reel Diameter	381 mm
Reel Material	Plastic
Parts Per Reel	250
Material	0.20 mm CRS Tin
Packaging	EIA-481
Co-planarity (Test LTWI-1119 & ANSI/JSTD-002)	< 0.10 mm
Solderability (Test MIL-STD-202 Method 208)	>99 %



Surface Mount Solderability (Test ANSI/EIA 638)	Passes
Appearance (Test LTIES-125)	Passes
Adhesion (Test ASTM B-571)	Passes
3 Axis Mechanical Shock (Test LTES-461)	Passes

[Print](#) [Back](#)