

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1654400](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



Extract from the online catalog

VS-PC-2XGOF-50-SCRJ/SCDU-1

Order No.: 1654400



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1654400>

Assembled fiber optic cable, break-out cable, glass fiber multi-mode 50/125 µm, SCRJ/IP20 on SC-duplex/IP20, for installation inside control cabinets, length: 1 m

Commercial data

| | |
|--------------------------|--------------------|
| EAN | 4017918970680 |
| Pack | 1 pcs. |
| Customs tariff | 85447000 |
| Weight/Piece | 0.07415 KG |
| Catalog page information | Page 216 (PC-2009) |

Product notes

WEEE/RoHS-compliant since:
11/09/2006



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Mechanical characteristics

| | |
|--------------------|------------------------------------|
| Connection profile | SCRJ according to DIN EN 50377-6-1 |
| Fiber type | Multimode glass fibers |
| Fiber | 50/125 µm |
| Ferrule diameter | 2.50 mm |

VS-PC-2XGOF-50-SCRJ/SCDU-1 Order No.: 1654400
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1654400>


| | |
|---|-------------------------------|
| Number of fibers | 2 |
| External cable diameter | Twin conductor (2.8 x 5.7 mm) |
| Type of cable | Break-out cable |
| Smallest bending radius, fixed installation | 60 mm |
| Smallest bending radius, movable installation | 60 mm |
| Length of cable | 1 m |
| Ambient temperature (operation) | -5 °C ... 70 °C |

Material data



| | |
|------------------------|-------------------|
| Housing material | PBT |
| Outer sheath, material | LSZH |
| External sheath, color | orange |
| Ferrule material | Zirconia ceramics |
| Ferrule holder color | White |
| Degree of protection | IP20 |

Diagrams/Drawings


Dimensioned drawing



SCRJ plug connector IP20



SC duplex connector IP20



VS-PC-2XGOF-50-SCRJ/SCDU-1 Order No.: 1654400
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1654400>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;