

Excellent Integrated System Limited

Stocking Distributor


Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Wintec Industries](#)
[SLM2434](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



HOME WHERE TO BUY CONTACT US
Search 

- CONSUMER
- OEM
- SUPPLY CHAIN MANAGEMENT
- DISTRIBUTION
- SUPPORT
- ABOUT WINTEC

Wintec > OEM

- Products ▾
 - ▶ DRAM
 - ▶ Solid State Drives
 - ▶ ADD2 Cards
 - ▶ Flash
 - ▶ Modems

EMBEDDED MODEMS

SLM EMBEDDED MODEM SERIES

SL EMBEDDED MODEM SERIES



SLM EMBEDDED MODEM SERIES

Wintec's embedded modem is based on a Silicon Labs ISO modem chipset. There is a long product history with this embedded modem at Wintec. Two different interfaces have been implemented for this product to meet various customer demands. One is a parallel mode interface where the data transactions between the host and the modem use an 8-bit data bus with a set of micro-controller control signals at the interface. The other uses a UART interface, where the embedded modem is operates in serial mode to handle data transfer with the host system.

Wintec is committed to long term support of embedded modems products. This includes maintaining long term product revisions, which allows communication and medical system customers the longevity of a product to pass FCC and FDA certifications. Wintec maintains two families of embedded modem products that span two generations of Silicon Labs modem chipsets.

Both generations of SLM embedded modems are in 2" x 1" DIP form factor and are often referred to as a DIP modems. There are 40 total number of pins in the DIP modem and each pin has a pin pitch of 0.1 inches.

Wintec also provides a 1.4" x 0.9" 24 pin small form factor solution. The smaller and more compact SL24xx Series modems support serial mode only. See SL Modem tab for more info.

1st Generation SLM Embedded Modem Series

PART NUMBER	Maximum Speed	Specification	Error Correction / Data Compression	FCC Certified
SLM2403	2.4Kbps	V.22bis	V.42, MNP2-4 / Not supported	Yes
SLM2414	14.4Kbps	V.32bis	V.42, MNP2-4 / V.42bis, MNP5	Yes
SLM2433	33.6Kbps	V.34	V.42, MNP2-4 / V.42bis, MNP5	Yes
SLM2456	56Kbps download / 33.6Kbps upload	V.90	V.42, MNP2-4 / V.42bis, MNP5	Yes

Note: For tacking firmware revision used by customer, Wintec may add "-xy" after the part number SLM24xx.

2nd Generation SLM Embedded Modem Series

PART NUMBER	Maximum Speed	Specification	Error Correction / Data Compression	FCC Certified
SLM2404	2.4Kbps	V.22bis	V.42, MNP2-4 / Not supported	Yes
SLM2415	14.4Kbps	V.32bis	V.42, MNP2-4 / V.42bis, MNP5	Yes
SLM2434	33.6Kbps	V.32bis	V.42, MNP2-4 / V.42bis, MNP5	Yes
SLM2457	56Kbps download / 33.6Kbps upload	V.90	V.42, MNP2-4 / V.42bis, MNP5	Yes
SLM2493	56Kbps download / 48Kbps upload	V.92	V.42, MNP2-4 / V.44, MNP5	Yes

Note: For tacking firmware revision used by customer, Wintec may add "-xy" after the part number SLM24xx.

