Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Wurth Electronics Inc 749196521

For any questions, you can email us directly: sales@integrated-circuit.com




Datasheet of 749196521 - TRANSFORMER 12UH 1.7A SMD


more than you expect


A Dimensions: [mm]












Scale - 1:1

B Recommended land pattern: [mm]



Scale - 1:1



D Electrical Properties:

Properties	Test conditions		Value	Unit	Tol.
Inductance base	10 kHz/ 1 V	L _{base}	12.0	μН	±20%
Turns ratio	N1:N2:N3:N4:N5:N6	n	1:1:1:1:1:1		
Rated Current base	$\Delta T = 40K$	I _{R base}	1.70	Α	typ.
Saturation Current base	IΔL/LI < 10%	I _{sat base}	1.73	Α	typ.
DC Resistance base	@ 20°C	R _{DC} base	71.1	mΩ	max.
Voltage-µSecond base		∫Udt _{base}	98.4	μVs	max.
Leakage Inductance base	10 kHz/ 1 V	L _{s base}	0.24	μН	typ.
Insulation test voltage	3 mA/1 s	U _T	500	V (AC)	

- I) Inductance of a single winding
 Pated Current of a single winding
 Saturation Current of a single winding
 Saturation Current of a single winding when all windings are driven.
 If not all windings are current driven the Saturation current per winding is 6x Isati_{passe} / number of driven windings
 4) DC Resistance of a single winding

E General information:

It is recommended that the temperature of the part does not exceed +125°C under worst case conditions.

- •Storage Temperature: -40°C to +85°C
- •Operating Temperature: -40°C to +125°C
- •Test conditions of Electrical Properties: 20°C, 33% RH if not specified differently

				Projection ————————————————————————————————————
				Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions
4.1	2014-02-18	SSt	TBr	Max-Eyth-Str. 1 74638 Waldenburg
4.0	2013-06-14	SSt	TBr	Germany Tel. +49 (0) 79 42 945 - 0
3.0	2006-08-01	TBr	-	www.we-online.com eiSos@we-online.com
REV	DATE	BY	CHECKED	GIOGNOTIC GIIIIIC.COIII

WE-FLEX Flexible Transformer for DC/DC Converter

Order - No

DESCRIPTION

749196521 Size: EFD20



This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover With Elektronic Resides Genified & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportation signal, desister prevention, medical, public information network etc.. With Elektronic & Ox Kip control, Transportat






more than you expect

WÜRTH ELEKTRONIK

C Schematic:



				Projection ————————————————————————————————————		DESCRIPTION		
				Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions		WE-FLEX Flexible Transformer for DC/DC Converter		S/DC
4.1	2014-02-18	SSt	TBr	Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com elSos@we-online.com		Order No.	COMPLIANT	SI7F
4.0	2013-06-14	SSt	TBr			740400504	ROHS&REACH	OIZE
3.0	2006-08-01	TBr	-			749196521	- IJAM ELEKTROMA	A4
REV	DATE	BY	CHECKED			Size: EFD20		

its electronic component has been designed and developed for usage in general electronic copipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

Browner With Elektronic RSSs Grinbl & Co KG products are neither designed nor intended for use in areas such as military, acrespace, avaitors, nucleous, outrity, it is incortion, it is incortion.

A defining a facility of the incortion o




Datasheet of 749196521 - TRANSFORMER 12UH 1.7A SMD

more than you expect

H Soldering Specifications:



H1: Classification Reflow Profile for SMT components:



H2: Classification Reflow Profiles

Profile Feature	Pb-Free Assembly
Preheat - Temperature Min (T _{smin}) - Temperature Max (T _{smax}) - Time (t _s) from (T _{smin} to T _{smax})	150°C 200°C 60-120 seconds
Ramp-up rate (T _L to T _P)	3°C/ second max.
Liquidous temperature (T_L) Time (t_L) maintained above T_L	217°C 60-150 seconds
Peak package body temperature (Tp)	See Table H3
Time within 5°C of actual peak temperature (tp)	20-30 seconds
Ramp-down rate (T _P to T _L)	6°C/ second max.
Time 25°C to peak temperature	8 minutes max.

refer to IPC/JEDEC J-STD-020D

H3: Package Classification Reflow Temperature

	Package Thickness	Volume mm³ <350	Volume mm ³ 350 - 2000	Volume mm³ >2000
PB-Free Assembly	< 1.6 mm	260°C	260°C	260°C
PB-Free Assembly	1.6 - 2.5 mm	260°C	250°C	245°C
PB-Free Assembly	≥ 2.5 mm	250°C	245°C	245°C

refer to IPC/JEDEC J-STD-020D

				Projection		DESCRIPTION		
						WE-FLEX Flexil	ble Transformer for DC	/DC
				Würth Elektronik eiSos GmbH 8 EMC & Inductive Solutions	& Co. KG	Converter		
4.1	2014-02-18	SSt	TBr	Max-Eyth-Str. 1 74638 Waldenburg		Order No.	COMPLIANT	SIZE
4.0	2013-06-14	SSt	TBr	Germany Tel. +49 (0) 79 42 945 - 0		740400504	ROHS&REACH	OIZE
3.0	2006-08-01	TBr	-	www.we-online.com eiSos@we-online.com		749196521	ELEKTRONIK	A4
REV	DATE	BY	CHECKED			Size: EFD20		

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

Notework With Elektronik elSos Orifish & Co KS products are neither designed or intended for use in a reas such as military, averageae, aution, uncleased or injury, averageae, aution, uncleased or information and an electronic information network etc. With Elektronik elSos Gridth & Co KS must be informed about the intent of such usage before the reference in a control, a substance in the safety of a substance in the safety of a substance in the safety of a legislation and product in the safety of a substance in the safety of a legislation and in the safety of a substance in the s



Datasheet of 749196521 - TRANSFORMER 12UH 1.7A SMD

more than you expect

I Cautions and Warnings:

The following conditions apply to all goods within the product series of WE-FLEX of Würth Elektronik eiSos GmbH & Co. KG:

All recommendations according to the general technical specifications of the data sheet have to be complied with.

The usage and operation of the product within ambient conditions, which probably alloy or harm the wire isolation, has to be avoided.

If the product is potted in customer applications, the potting material might shrink during and after hardening. The product is exposed to the pressure of the potting material with the effect that the core, wire and termination is possibly damaged by this pressure and so the electrical as well as the mechanical characteristics are endangered to be affected. After the potting material is cured, the core, wire and termination of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply to customer specific products.

Cleaning agents that are used to clean the customer application might damage or change the characteristics of the component, body, pins or

Direct mechanical impact to the product shall be prevented as the ferrite material of the core could flake or in the worst case it could break.

Product specific:

- Follow all instructions mentioned in the data sheet, especially:

 •The soldering profile has to be complied with according to the technical reflow soldering specification, otherwise this will void the warranty.

 - war largy.

 Wave soldering is not applicable. Reflow soldering is recommended.

 •All products shall be used before the end of the period of 12 months based on the product date code, if not a 100% solderability can't be
- Violation of the technical product specifications such as exceeding the nominal rated current will void the warranty.

				Projection		DESCRIPTION		
						WE-FLEX Flexil	ble Transformer for DC	/DC
				Würth Elektronik eiSos Gmbl EMC & Inductive Solutions	H & Co. KG	Converter		
4.1	2014-02-18	SSt	TBr	Max-Eyth-Str. 1 74638 Waldenburg		Order No.	COMPLIANT	SIZE
4.0	2013-06-14	SSt	TBr	Germany Tel. +49 (0) 79 42 945 - 0		740400504	ROHS&REACH	OLL
3.0	2006-08-01	TBr	-	www.we-online.com eiSos@we-online.com		749196521		A4
REV	DATE	BY	CHECKED	GIOGGONG GIIIIIC.COIII		Size: EFD20		

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wilm Elektronic Resides Genified X to XIS grounds are neither designed not intended for use in a reasonable, and a reliability standard in electronic experts, in a partie or intended for use in a reasonable personable personable or intended for use in a reasonable personable pers





Datasheet of 749196521 - TRANSFORMER 12UH 1.7A SMD

more than you expect

J Important Notes:

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications
It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications

In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component.

Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty,

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve spe cific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected



6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered.

The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights
All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG.

Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

				Projection	DESCRIPTION
				- □	WE-FLEX Flexible Transformer for DC/DC
				Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions	Converter
4.1	2014-02-18	SSt	TBr	Max-Eyth-Str. 1 74638 Waldenburg	Order No. COMPLIANT SIZE
4.0	2013-06-14	SSt	TBr	Germany Tel. +49 (0) 79 42 945 - 0	ROHS&REACH WORTH BLEXTRONIK
3.0	2006-08-01	TBr	-	www.we-online.com eiSos@we-online.com	749196521 WORTH ELEKTRONIK A4
REV	DATE	BY	CHECKED	elous@we-utilite.cutt	Size: EFD20

nent has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

Similar Schrift & Ch. KS products are neither designed not intended for use in a rease such as military, acrespace, aviation, nuclear control, similarine, transportation is spraced, this careful, transportation signal, disaster prevention, medical, public information network etc., Will'im Elektronik eSos Gritch & Ch. KG must be informed about the internet of such usage before addition, sufficient reliability healuration checks for seller years be performed on every electronic component which is useful network calculations transportation in a control of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

Similar Schrift & Ch. KS products are network expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

Similar Schrift & Ch. KS products are network expected to cause severe personal injury or death, unless the parties that the part