



Date	SYM	REVISION RECORD	AUTH	DR.	CK.
12/05/08	A	ADDED ROHS COMPLIANT	T.B.	B.S.	
08/01/14	B	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	




NOTES:

1. MATERIAL:

HOUSING : BLACK POLYPROPYLENE  
 FLAMMABILITY RATING -UL94-HB, UL FILE NO. E216959  
 TEMPERATURE RANGE: -10°C to +100°C  
 WIRES: 26 AWG, UL1007, CSA-TR-64, 300V, 80°C  
 RIVETS: BRASS, NICKEL PLATED.  
 SPRING: SPRING STEEL, NICKEL PLATED.  
 CONTACT RESISTANCE: UNDER 50mΩ FOR +/- CONTACTS PER EIA-540J000

ROHS 2 COMPLIANT.

Tolerance (Except as noted)	 <b>Memory Protection Devices, Inc</b> 200 Broad Hollow Road, Farmingdale, New York 11735	Scale	Drawn By B.S.
			Approved By T.B.
decimal ±.5 (.020)	Title FOUR "D" CELL HOLDER WITH 6" WIRE LEADS		
Fractional ± .8 (.030)	Date 08/01/14	Drawing Number BH4DW	
Angular ± 3°			