

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Chip Quik](#)  
[SMDFP-2S-2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

## FP-2S-2

### MicroGripper - 0.5mm to 0.2mm Lead Pitch

#### Features

- Used with SMT packages down to 0.2mm lead pitch
- Thin clip body width allows many lead Grippers to be mounted side-by-side for simultaneous testing
- Maximum frequency is 100MHz



#### SPECIFICATIONS

<b>Temperature Range:</b>	0-70°C
<b>Conductor Resistance:</b>	60 mOhms
<b>Contact Resistance:</b>	10 mOhms
<b>Tines Diameter:</b>	0.08mm
<b>Body Height:</b>	14mm
<b>Body Material:</b>	ABS
<b>Voltage Usage:</b>	+/-40V
<b>Rating:</b>	500 WVDC
<b>Bandwidth:</b>	(3db) >100MHz
<b>Inductance:</b>	< 1mH @ 1KHz
<b>Capacitance:</b>	< 2.0pF @ 1KHz
<b>Material:</b>	Steel wire or stainless steel, Nickel-plated

#### DIMENSIONS

