

Excellent Integrated System Limited

Stocking Distributor



Click to view price, real time Inventory, Delivery & Lifecycle Information:

[On-Shore Technology, Inc.](#)


[OSTVF045050](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



N= Number of poles



P.C.B LAYOUT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

SIGN	DATE	DESCRIPTION	APPROVER

Material

- Contact pin: Brass
- Surface of solder tail: Tin plated
- Insulator (housing): Thermoplastic (UL94V-0)

Electrical

- Voltage rating: 300VAC
- Current rating: 15A
- Withstanding Voltage: 1.6KV
- Operating temperature: -30°C to +105°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety approval: us

RoHS Compliant

PART NUMBER:

OSTVFXX5050

No. of Poles →

- 04: 2x02 Poles
- 06: 2x03 Poles
- : :
- 48 2x24 Poles

COLOR

- 0: Black
- 5: Green (Standard)
- 6: Blue
- 8: Grey



ON-SHORE TECHNOLOGY, INC.

TITLE: OSTVF-5.08mm Series open vertical 2x2p-2x24p				DWG NO. OSTVFXX5050.DWG	
PART NO. OSTVFXX5050		CUST NO.		Tolerance	
APPROVED	CHECKED	DESIGNED	DRAWN		X ±0.50
Shi Jun 2006.11.07	Marvin 2006.11.07	Marvin 2006.11.07	Marvin 2006.11.07		X.X ±0.30
SHEET: 01/01				UNIT: mm	X.XX ±0.10
REV: C				SCALE: NONE	X* ±1*