Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

International Rectifier (Infineon Technologies Americas Corp.)
IRF9388TRPBF

For any questions, you can email us directly:
sales@integrated-circuit.com

Distributor of International Rectifier (Infineon Technologies Americas Corp.): Excellent In
Datasheet of IRF9388TRPBF - MOSFET P-CH 30V 12A 8-SOIC
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

International
IOR Rectifier

PD - 97521

IRF9388PbF

HEXFET® Power MOSFET

V_{DS}	-30	V
$V_{GS\ max}$	±25	V
$R_{DS(on)\ max}$ (@V_{GS} = -10V)	11.9	mΩ
I_D (@T_A = 25°C)	-12	A





Applications

- Adaptor Input Switch for Notebook PC

Features and Benefits

Features	Resulting Benefits
25V V_{GS} max	Direct Drive at High V_{GS}
Industry-Standard SO8 Package	Multi-Vendor Compatibility
RoHS Compliant Containing no Lead, no Bromide and no Halogen	Environmentally Friendlier

Orderable part number	Package Type	Standard Pack		Note
		Form	Quantity	
IRF9388PbF	SO8	Tube/Bulk	95	
IRF9388TRPbF	SO8	Tape and Reel	4000	

Absolute Maximum Ratings

	Parameter	Max.	Units
V_{DS}	Drain-to-Source Voltage	-30	V
V_{GS}	Gate-to-Source Voltage	± 25	
I_D @ T_A = 25°C	Continuous Drain Current, V_{GS} @ 10V	-12	A
I_D @ T_A = 70°C	Continuous Drain Current, V_{GS} @ 10V	-9.6	
I_{DM}	Pulsed Drain Current ①	-96	
P_D @T_A = 25°C	Power Dissipation ④	2.5	W
P_D @T_A = 70°C	Power Dissipation ④	1.6	
	Linear Derating Factor	0.02	W/°C
T_J T_{STG}	Operating Junction and Storage Temperature Range	-55 to + 150	°C

Notes ① through ⑥ are on page 2

Distributor of International Rectifier (Infineon Technologies Americas Corp.): Excellent In
Datasheet of IRF9388TRPBF - MOSFET P-CH 30V 12A 8-SOIC
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Static @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	-30	—	—	V	V_{GS} = 0V, I_D = -250µA
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	—	0.021	—	V/°C	Reference to 25°C, I_D = -1mA
$R_{DS(on)}$	Static Drain-to-Source On-Resistance	—	8.5	—	mΩ	V_{GS} = -20V, I_D = -12A ③
		—	10	11.9		V_{GS} = -10V, I_D = -12A ③
$V_{GS(th)}$	Gate Threshold Voltage	-1.3	-1.8	-2.4	V	V_{DS} = V_{GS}, I_D = -25µA
$\Delta V_{GS(th)}$	Gate Threshold Voltage Coefficient	—	-5.8	—	mV/°C	
I_{DSS}	Drain-to-Source Leakage Current	—	—	-1.0	µA	V_{DS} = -24V, V_{GS} = 0V
		—	—	-150		V_{DS} = -24V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Forward Leakage	—	—	10	µA	V_{GS} = -25V
	Gate-to-Source Reverse Leakage	—	—	10		V_{GS} = 25V
gfs	Forward Transconductance	20	—	—	S	V_{DS} = -10V, I_D = -9.6A
Q_g	Total Gate Charge ⑥	—	18	—	nC	V_{DS} = -15V, V_{GS} = -4.5V, I_D = - 9.6A
Q_g	Total Gate Charge ⑥	—	35	52	nC	V_{GS} = -10V
Q_{gs}	Gate-to-Source Charge ⑥	—	5.3	—		V_{DS} = -15V
Q_{gd}	Gate-to-Drain Charge ⑥	—	8.5	—		I_D = -9.6A
R_G	Gate Resistance ⑥	—	15	—	Ω	
$t_{d(on)}$	Turn-On Delay Time	—	19	—	ns	V_{DD} = -15V, V_{GS} = -4.5V ③
t_r	Rise Time	—	57	—		I_D = -1.0A
$t_{d(off)}$	Turn-Off Delay Time	—	80	—		R_G = 6.8Ω
t_f	Fall Time	—	66	—		See Figs. 20a &20b
C_{iss}	Input Capacitance	—	1680	—	pF	V_{GS} = 0V
C_{oss}	Output Capacitance	—	350	—		V_{DS} = -25V
C_{rss}	Reverse Transfer Capacitance	—	220	—		f = 1.0MHz

Avalanche Characteristics

	Parameter	Typ.	Max.	Units
E_{AS}	Single Pulse Avalanche Energy ②	—	120	mJ
I_{AR}	Avalanche Current ①	—	-9.6	A

Diode Characteristics

	Parameter	Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current (Body Diode)	—	—	-2.5	A	MOSFET symbol showing the integral reverse p-n junction diode.
I_{SM}	Pulsed Source Current (Body Diode) ①	—	—	-96		
V_{SD}	Diode Forward Voltage	—	—	-1.2	V	T_J = 25°C, I_S = -2.5A, V_{GS} = 0V ③
t_{rr}	Reverse Recovery Time	—	51	76	ns	T_J = 25°C, I_F = -2.5A, V_{DD} = -24V
Q_{rr}	Reverse Recovery Charge	—	35	53	nC	di/dt = 100A/µs ③

Thermal Resistance

	Parameter	Typ.	Max.	Units
$R_{\theta JL}$	Junction-to-Drain Lead ⑤	—	20	°C/W
$R_{\theta JA}$	Junction-to-Ambient ④	—	50	

Notes:

① Repetitive rating; pulse width limited by max. junction temperature.

② Starting T_J = 25°C, L = 2.6mH, R_G = 25Ω, I_{AS} = -9.6A.

③ Pulse width ≤ 400µs; duty cycle ≤ 2%.

④ When mounted on 1 inch square copper board.

⑤ R_θ is measured at T_J of approximately 90°C.

⑥ For DESIGN AID ONLY, not subject to production testing.

Distributor of International Rectifier (Infineon Technologies Americas Corp.): Excellent In
Datasheet of IRF9388TRPBF - MOSFET P-CH 30V 12A 8-SOIC
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. Typical Transfer Characteristics



Fig 4. Normalized On-Resistance vs. Temperature



Fig 5. Typical Capacitance vs.Drain-to-Source Voltage



Fig 6. Typical Gate Charge vs.Gate-to-Source Voltage

Distributor of International Rectifier (Infineon Technologies Americas Corp.): Excellent In
Datasheet of IRF9388TRPBF - MOSFET P-CH 30V 12A 8-SOIC
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com



Fig 7. Typical Source-Drain Diode Forward Voltage



Fig 8. Maximum Safe Operating Area



Fig 9. Maximum Drain Current vs. Ambient Temperature



Fig 10. Threshold Voltage vs. Temperature



Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

Distributor of International Rectifier (Infineon Technologies Americas Corp.): Excellent In
Datasheet of IRF9388TRPBF - MOSFET P-CH 30V 12A 8-SOIC
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com



Fig 12. On-Resistance vs. Gate Voltage



Fig 13. Typical On-Resistance vs. Drain Current



Fig 14. Maximum Avalanche Energy vs. Drain Current



Fig 16. Typical Power vs. Time



* Reverse Polarity of D.U.T for P-Channel



* V_{GS} = 5V for Logic Level Devices

Fig 17. Diode Reverse Recovery Test Circuit for P-Channel HEXFET® Power MOSFETs

Distributor of International Rectifier (Infineon Technologies Americas Corp.): Excellent In
Datasheet of IRF9388TRPBF - MOSFET P-CH 30V 12A 8-SOIC
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com



Fig 18a. Gate Charge Test Circuit



Fig 18b. Gate Charge Waveform



Fig 19a. Unclamped Inductive Test Circuit



Fig 19b. Unclamped Inductive Waveforms



Fig 20a. Switching Time Test Circuit



Fig 20b. Switching Time Waveforms

SO-8 Package Outline (Mosfet & Fetky)

Dimensions are shown in milimeters (inches)



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.0532	.0688	1.35	1.75
A1	.0040	.0098	0.10	0.25
b	.013	.020	0.33	0.51
c	.0075	.0098	0.19	0.25
D	.189	.1968	4.80	5.00
E	.1497	.1574	3.80	4.00
e	.050 BASIC		1.27 BASIC	
e 1	.025 BASIC		0.635 BASIC	
H	.2284	.2440	5.80	6.20
K	.0099	.0196	0.25	0.50
L	.016	.050	0.40	1.27
y	0°	8°	0°	8°





NOTES:

1. DIMENSIONING & TOLERANCING PER ASME Y14.5M-1994.
2. CONTROLLING DIMENSION: MILLIMETER
3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AA.
5. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.15 [.006].
6. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.25 [.010].
7. DIMENSION IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE.

FOOTPRINT



SO-8 Part Marking Information

EXAMPLE: THIS IS AN IRF7101 (MOSFET)



Note: For the most current drawing please refer to IR website at http://www.irf.com/package/

IRF9388PbF

International
IOR Rectifier

SO-8 Tape and Reel (Dimensions are shown in milimeters (inches))



NOTES:
1. CONTROLLING DIMENSION : MILLIMETER.
2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS(INCHES).
3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



NOTES :
1. CONTROLLING DIMENSION : MILLIMETER.
2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Qualification Information†

Qualification level	Consumer ††	
	(per JEDEC JESD47F††† guidelines)	
Moisture Sensitivity Level	SO-8	MSL1 (per JEDEC J-STD-020D†††)
RoHS Compliant	Yes	

† Qualification standards can be found at International Rectifier's web site
http://www.irf.com/product-info/reliability

†† Higher qualification ratings may be available should the user have such requirements.
Please contact your International Rectifier sales representative for further information:
http://www.irf.com/whoto-call/salesrep/

††† Applicable version of JEDEC standard at the time of product release.

Data and specifications subject to change without notice.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.6/2010