

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Hammond Manufacturing](#)  
[291DX](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

291DX

**NOTE: ALL LEADS 9" OUT MIN., STRIPPED .5"**

DIMENSIONS:	
A	3.438" ±0.063
B	4.063" ±0.125
C	4.125" ±0.063
D	1.844" ±0.063
E	2.750" ±0.063
F	3.438" ±0.063

PRIMARY	SECONDARY
BLK	325V RED
	650VCT
	50V RED/GRN
	0V RED/YEL
BLK	230mA
	325V RED
	YEL
	5V
	3A
	YEL
	GRN
	6.3VCT
	GRN/WHT
	4A
	GRN
ORG	SH

ELECTRICAL DATA:	
Turns ratio:	1 : 5.94 ( RED - RED)
Exciting Current	@ 120V, 60Hz, BLK - BLK = 282mA Max.
DCR	@ 20C, BLK - BLK = 1.262 Ω ±20%
	@ 20C, RED - RED = 70.27 Ω ±20%
	@ 20C, YEL - YEL = 0.071 Ω ±20%
	@ 20C, GRN - GRN = 0.058 Ω ±20%
Pri. Voltage	120V 50Hz
Sec. Voltage (RMS)	650VCT @ 230mA C/W 50V TAP, 5V @ 3A / 6.3VCT @ 4A
No Load Voltage	712.29VCT / 5.30V / 6.75V

**HAMMOND ELECTRONICS**  
52 RANKIN PLACE,  
WATERLOO, ONTARIO, N2L 3Z5.  
PHONE: (519) 886-6181  
FAX # (519) 886-9540

TITLE			
<b>291DX</b>			
		DR BY	B.Pervaiz
		DATE	08/25/09
NO	DATE	REVISION	DIM IN(Ø)MM( )

291DX