

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1503344](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog


SACB- 8X0,34/ 3X0,75-50,0 PUR

Order No.: 1503344



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1503344>

Master cable for sensor/actuator boxes, with PE conductor, unshielded, material PUR/PVC, 11-pos., 8 x 0.34 mm² and 3 x 0.75 mm²

Commercial data	
GTIN (EAN)	 4 017918 896942
Note	Made-to-order
sales group	D192
Pack	1 pcs.
Customs tariff	85366990
Catalog page information	Page 135 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
05/24/2006



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
General data	
Rated voltage	300 V
Master cable data	
Length of cable	50 m

SACB- 8X0,34/ 3X0,75-50,0 PUR Order No.: 1503344

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1503344>

Cable type	Master cable suitable for flexible cable conduit
Signal line cross section	8x 0.34 mm ²
AWG signal line	22
Conductor structure signal line	42x 0.10 mm
Power supply cross section	3x 0.75 mm ²
AWG power supply	19
Conductor structure, voltage supply	96x 0.10 mm
External diameter	9.2 mm
Max. bending cycles	1500000
Bending radius	95 mm
Traversing path	2 m
Traversing rate	2 m/s
Ambient temperature (operation)	-40 °C ... 90 °C (for fixed installation)
	-5 °C ... 80 °C (for flexible installation)

Accessories

Item	Designation	Description
Tools		
1212156	WIREFOX 4	Stripping tool, for lines and conductors (special for rubber and silicon insulations) of 0.1 - 4 mm ² , self-adjusting, stripping length up to 18 mm, cutting capacity up to 10 mm ² stranded / 1.5 mm ² solid
1212162	WIREFOX-D 13	Stripping tool, for stripping installation lines of Ø 8 - 13 mm , e.g. NYM 3 x 1.5 mm ² to 5 x 2.5 mm ² , single line stripping 0.2 mm ² - 4 mm ² , with longitudinal cut blade and sliding knife
1212161	WIREFOX-D 40	Stripping tool, for stripping lines of Ø 4.5 - 40 mm, insulation strength up to 4.5 mm

SACB- 8X0,34/ 3X0,75-50,0 PUR Order No.: 1503344

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1503344>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;