

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1525869](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

SACC-E-M12FS-4CON-SQ26/ 0,5


Order No.: 1525869



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1525869>

Sensor/Actuator flush-type socket, 4-pos., M12, A-coded, front/square flange mounting, with 0.5 m TPE litz wire, 4 x 0.34 mm²

Commercial data

GTIN (EAN)	 4 046356 022491
sales group	D125
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 38 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
06/09/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Rated current at 40°C	4 A
Rated voltage	250 V
Number of positions	4
Volume resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ

SACC-E-M12FS-4CON-SQ26/ 0,5 Order No.: 1525869
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1525869>

Length of cable	0.5 m
Ambient temperature (operation)	-25 °C ... 85 °C (Male connector / female connector)

General characteristics

Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP54
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA66 GF
Material, knurls	Nickel-plated brass
Sealing material	NBR
Mounting type	Front mounting Square flange
Type of connection	Individual wires
Status display	No

Conductor data

Cable type	TPE litz wire
Conductor cross section	0.34 mm ²
AWG signal line	22
Conductor structure signal line	7x 0.25 mm
Core diameter including insulation	1.2 mm ±0.07 mm
Thickness, insulation	0.21 mm (Core insulation)
Wire colors	Black, brown, blue, white
Insulation resistance	≥ 20 MΩ*km
Conductor resistance	≤ 57.6 mΩ/m
Nominal voltage, conductor	300 V
Test voltage, conductor	2000 V AC
Material conductor insulation	TPE
Conductor material	Tin-plated Cu litz wires
Ambient temperature (operation)	-25 °C ... 90 °C (cable, fixed installation)

Certificates / Approvals


SACC-E-M12FS-4CON-SQ26/ 0,5 Order No.: 1525869


<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1525869>

Certification

UL


Diagrams/Drawings

Dimensioned drawing




M12 flush-type connector

Circuit diagram



Contact assignment of the M12 socket

Schematic diagram



Pin assignment M12 socket, 4-pos., A-coded, view female side

SACC-E-M12FS-4CON-SQ26/ 0,5 Order No.: 1525869
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1525869>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;