

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[1644973](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog

## HC-B 10-TFL-72/O1STM25S


Order No.: 1644973



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1644973>

HEAVYCON sleeve housing B10, for single locking latch, height 72 mm, without support 1x M25, lateral conductor exit

### Commercial data

GTIN (EAN)	 4 017918 912819
sales group	D002
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 482 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
03/03/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

HC-B 10-TFL-72/O1STM25S Order No.: 1644973

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1644973>


**Technical data**

**General data**

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Design	B10
Height	72 mm
Width	43 mm
Length	73 mm
Housing type	Sleeve housings
Locking type	for single locking latch
Cable exit	Lateral
Type of the screw connection	1x M25
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray

**Diagrams/Drawings**

Dimensioned drawing



HC-B 10-TFL-72/O1STM25S Order No.: 1644973

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1644973>

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;