

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[1646337](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog


## HC-B 24-SML-68/O1M25

Order No.: 1646337



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1646337>

HEAVYCON box mounting base B24, with single locking latch, height 68 mm, with support 1x M25

Commercial data	
GTIN (EAN)	 4 017918 961831
sales group	D002
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 497 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
03/01/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

General data	
Note	For contact inserts HC-B24, BB46, D64, DD108, M
Design	B24
Height	68 mm
Width	57 mm
Length	144 mm


HC-B 24-SML-68/O1M25 Order No.: 1646337

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1646337>

Housing type	Box mounting bases
Locking type	With single locking latch
Cable exit	Conductor exit direction to the left (looking into the open single locking latch)
Type of the screw connection	1x M25
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Material lock	High-grade steel, handle: PA-GF
Material grip body interlock	PA-GF

### Diagrams/Drawings

Dimensioned drawing



HC-B 24-SML-68/O1M25 Order No.: 1646337

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1646337>

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;