

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1674273](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog


HC-B 24-TFL-76/O1PG29S

Order No.: 1674273



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674273>

Sleeve housing, for single locking latch, height 76 mm, without screw connection, 1x Pg29, lateral cable entry

Commercial data	
GTIN (EAN)	 4 017918 152222
sales group	D002
Pack	10 pcs.
Customs tariff	85389099

Product notes

WEEE/RoHS-compliant since:
03/01/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Note	For contact inserts HC-B24, BB46, D64, DD108, M
Design	B24
Height	76 mm
Width	43 mm

HC-B 24-TFL-76/O1PG29S Order No.: 1674273
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674273>

Length	120 mm
Housing type	Sleeve housings
Locking type	for single locking latch
Cable exit	Lateral
Type of the screw connection	1x Pg29
Pg screw connection	None
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray


Certificates / Approvals



Certification GOST

Diagrams/Drawings

Dimensioned drawing



HC-B 24-TFL-76/O1PG29S Order No.: 1674273

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674273>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;