

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[1604847](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog

## HC-B 24-TFQ-56/O1M25G


Order No.: 1604847



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604847>

HEAVYCON sleeve housing B24, for double locking latch, height 56 mm, with support 1x M25, straight conductor exit

### Commercial data

GTIN (EAN)	 4 017918 881917
sales group	D002
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 498 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
03/01/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General data

Note	For contact inserts HC-B24, BB46, D64, DD108, M
Design	B24
Height	56 mm
Width	43 mm

HC-B 24-TFQ-56/O1M25G Order No.: 1604847

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604847>

Length	120 mm
Housing type	Sleeve housings
Locking type	For double locking latch
Cable exit	Straight
Type of the screw connection	1x M25
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray

### Certificates / Approvals




Certification

GOST

### Diagrams/Drawings

Dimensioned drawing



HC-B 24-TFQ-56/O1M25G Order No.: 1604847

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604847>

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;