

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1585605](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



Extract from the online catalog


HC-M-04-MOD-BUC

Order No.: 1585605



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1585605>

HEAVYCON contact insert module, socket, 4-pos. to 40 A, crimp connection

Commercial data	
GTIN (EAN)	 4 046356 290043
sales group	D042
Pack	2 pcs.
Customs tariff	85369010
Catalog page information	Page 455 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
08/01/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Electrical characteristics	
Note	for housing HC-B6 to B48, for housing HC-ADVANCE-B6 to B24, hinged retaining frame HC-M-MHR... necessary, crimp connection (crimp contacts not included in scope of supply)
Rated voltage (III/3)	830 V
Rated current	40 A

HC-M-04-MOD-BUC Order No.: 1585605

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1585605>

Rated surge voltage	8 kV
Ambient temperature (operation)	-40 °C ... 125 °C
Number of positions	4

Mechanical characteristics

Conductor cross-section	1.5 mm ² ... 6 mm ²
Connection cross-section AWG	16 ... 10
Stripping length of the individual wire	9 mm (9.6 mm (4-6 mm ²))
	9.6 mm (4 mm ² ... 6 mm ²)
Insertion/withdrawal cycles	≥ 500

General characteristics

Number of module slots	1
Connection method	Crimp connection
Inflammability class acc. to UL 94	V0
Pollution degree	3
Surge voltage category	III
Assembly instructions	For housing heights ≥ 52 mm. Plug-in connections may only be operated only when there is no load/voltage.
Connection	The module cannot be used simultaneously with the HC-B..-TMB-SD-IP65 and HC-B..-TMS-SD-IP65 protective covers.

Material data

Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PC


Certificates / Approvals


Certification UL

HC-M-04-MOD-BUC Order No.: 1585605
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1585605>


Diagrams/Drawings

Diagram



Derating diagram (6 modules in HC-B 24 housing)

Dimensioned drawing




Socket module

HC-M-04-MOD-BUC Order No.: 1585605

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1585605>

Schematic diagram

Connector pin assignment, connection side



HC-M-04-MOD-BUC Order No.: 1585605

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1585605>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;