

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1644902](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



Extract from the online catalog

HC-WRV-M25

Order No.: 1644902

The illustration shows the version HC-WRV-PG 21



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1644902>

Corrugated tube screw connection, for corrugated tubes, to lead individual conductors and wires with IP65 protection into the housings of the HEAVYCON industrial connectors, M25

Commercial data	
GTIN (EAN)	 4 017918 911188
sales group	D096
Pack	10 pcs.
Customs tariff	39174000
Catalog page information	Page 557 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
10/31/2006



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data


General data	
Cable gland material	PA
Inflammability class acc. to UL 94	HB
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 110 °C

HC-WRV-M25 Order No.: 1644902

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1644902>

Diagrams/Drawings

Dimensioned drawing



Assembly instructions for M25 corrugated pipe

a = Corrugated screw connection

b = Corrugated pipe

c = Opener

Installation note:

Cut the corrugated pipe in the groove to retain a round shape for insertion. The lighter seal (not depicted in the illustration) is positioned in the corrugated pipe screw connection below the safety latch. The darker outer seal (not depicted in the illustration) is placed over the corrugated pipe screw connection from outside. The corrugated pipe is then pushed as far as possible into the corrugated pipe screw connection and clicks into place. The screw connection is opened by placing the yellow corrugated pipe opener with force between the safety latch and the corrugated tube and the corrugated pipe is then pulled out.

HC-WRV-M25 Order No.: 1644902
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1644902>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;