

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[1674969](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog

# CK1,6-ED-0,37BU AU

Order No.: 1674969



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674969>

Turned 1.6 crimp contact, individual female contact, core diameter 0.14 to 0.37 mm<sup>2</sup>, gold-plated

Commercial data	
GTIN (EAN)	 4 017918 135669
sales group	D090
Pack	100 pcs.
Customs tariff	85366990
Catalog page information	Page 528 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
12/01/2005



<http://www.download.phoenixcontact.com>  
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### Electrical characteristics

Note	For HC-M-12, HC-M-EMC, HC-D, HC-DD and VC-D contact inserts, the quality of a crimp connection is determined by DIN EN 60 352-2, gold-plated contacts recommended at U > 5 V and I > 5 mA
Ambient temperature (operation)	-40 °C ... 125 °C

CK1,6-ED-0,37BU AU Order No.: 1674969

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674969>

**Mechanical characteristics**

Conductor cross-section	0.14 mm <sup>2</sup> ... 0.37 mm <sup>2</sup>
Connection cross-section AWG	22 ... 24
Stripping length of the individual wire	8 mm (6 mm in case of 2.5 mm <sup>2</sup> )
Insertion/withdrawal cycles	≥ 500

**General characteristics**

Type	Individual female contact
Series	HC-M-12
Connection method	Crimp connection

**Material data**

Contact material	Copper alloy
Contact surface material	Hard gold-plated

**Certificates / Approvals**



Certification GOST, UL

**Accessories**


Item	Designation	Description
<b>General</b>		
1884869	VC-EW 1,6	Contact removal tool, for turned and rolled CK- 1.6-... contacts
<b>Tools</b>		
1676734	CK1,6/2,5-MWZ	Assembly tool, for CK 1.6... crimp contacts for small conductor cross sections
1687419	CRIMPFOX-1,6/2,5-ED-4,0	Crimping pliers, for turned contacts, CK 1.6 ED... and CK 2.5 ED...

CK1,6-ED-0,37BU AU Order No.: 1674969

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674969>

## Diagrams/Drawings

Dimensioned drawing



CK1,6-ED-0,37BU AU Order No.: 1674969

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674969>

---

#### Address

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;