

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[2290863](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog

## FLK 14/EZ-DR/ 600/KONFEK

Order No.: 2290863


The illustration shows a 50-pos. version



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2290863>

Round cable set, with two 14-pos. socket strips (1:1 connection), for connecting 8 channels, cable length: 6 m

### Commercial data

GTIN (EAN)	 4 017918 058227
sales group	I680
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 262 (IF-2009)

### Product notes

WEEE/RoHS-compliant since:  
05/26/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General

Nominal voltage $U_N$	< 50 V AC
	60 V DC
Max. current carrying capacity per path	1 A
Max. conductor resistance	0.16 $\Omega$ /m
Ambient temperature (operation)	-20 °C ... 50 °C

FLK 14/EZ-DR/ 600/KONFEK Order No.: 2290863

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2290863>

Ambient temperature (storage/transport)	-20 °C ... 70 °C
Number of positions	14
Number of positions, control side	14
Number of connectors, control side	1
Number of positions, module side	14
Number of connectors, modul side	1
Fixed cable length	6 m
Single wire, cross section	0.14 mm <sup>2</sup>
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	6.4 mm
Cable, preassembly	Insulation displacement, IEC 60352-4/DIN EN 60352-4
Shielding	no

#### Certificates / Approvals



Certification

CUL, GOST, UL

FLK 14/EZ-DR/ 600/KONFEK Order No.: 2290863

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2290863>

---

#### Address

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;