

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2296692](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

FLK 50/4X14/EZ-DR/ 100/KONFEK

Order No.: 2296692



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2296692>

Round cable set, for connection to the VARIOFACE system cabling, with a 50-position socket strip and four 14-position socket strips, for splitting max. 32 channels into 4 x 8 channels, no. of positions: 50/ 4 x 14, cable length 1.0 m

| Commercial data | |
|--------------------------|---------------------|
| GTIN (EAN) | 4 017918 593773 |
| sales group | I680 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |
| Catalog page information | Page 266 (IF-2009) |

Product notes

WEEE/RoHS-compliant since:
03/09/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

| General | |
|---|-----------|
| Nominal voltage U_N | < 50 V AC |
| | 60 V DC |
| Max. current carrying capacity per path | 1 A |

FLK 50/4X14/EZ-DR/ 100/KONFEK Order No.: 2296692

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2296692>

| | |
|---|---|
| Max. conductor resistance | 0.16 Ω/m |
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Number of positions, control side | 50 |
| Number of connectors, control side | 1 |
| Number of positions, module side | 14 |
| Number of connectors, modul side | 4 |
| Fixed cable length | 1 m |
| Single wire, cross section | 0.14 mm ² |
| AWG | 26 |
| Conductor construction: Number of litz wires: | 7 |
| Single wire, material | Cu tin-plated |
| External diameter | 6.3 mm |
| Cable, preassembly | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding | no |

Certificates / Approvals



Certification

CUL, GOST, UL

FLK 50/4X14/EZ-DR/ 100/KONFEK Order No.: 2296692
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2296692>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;