

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[5528354](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



Extract from the online catalog

FLKM HDSUB-26/M


Order No.: 5528354



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=5528354>

VARIOFACE module, with screw connection and high density D-Subminiature male connector, for mounting on NS 32 or NS 35/7.5, no. of pos.: 26, width: 79 mm

Commercial data

GTIN (EAN)	 4 017918 957841
sales group	I011
Pack	1 pcs.
Customs tariff	85369010
Catalog page information	Page 253 (IF-2007)

<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Nominal voltage U_N	125 V
Max. current carrying capacity per branch	1 A
Number of positions	26
Width	79 mm
Height	77 mm
Depth	58 mm
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any

FLKM HDSUB-26/M Order No.: 5528354


<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=5528354>

Connection data

Connection 1	PCB connection
Connection in acc. with standard	IEC / EN
Type of connection	Screw connection
Number of positions	26
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M3
Connection 2	D-SUB connection
Type of connection	Pluggable

Diagrams/Drawings


Circuit diagram



FLKM HDSUB-26/M Order No.: 5528354

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=5528354>

Schematic diagram



FLKM HDSUB-26/M Order No.: 5528354

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=5528354>

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;