

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[2261038](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog


## SKBI 32/C

Order No.: 2261038



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2261038>

Plug-in card block, Nominal current: 4 A, Number of positions: 32, Pitch: 0 mm, Color: green

Commercial data	
GTIN (EAN)	 4 017918 053819
sales group	E211
Pack	1 pcs.
Customs tariff	85369010
Catalog page information	Page 522 (CC-2009)

### Product notes

WEEE/RoHS-compliant since:  
06/06/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

Dimensions / positions	
Length	43 mm
Height	138 mm
Width	112 mm
Pitch	0 mm
Number of positions	32

SKBI 32/C Order No.: 2261038

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2261038>

Hole diameter	4.2 mm
Screw thread	M3
Tightening torque, min	0.5 Nm
Tightening torque max	0.6 Nm

**Technical data**

Range of articles	SKBI 32
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	4 A
Nominal voltage $U_N$	250 V
Stripping length	8 mm

**Connection data**

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

**Certificates / Approvals**



Certification GOST

**Accessories**

Item	Designation	Description
------	-------------	-------------

**Assembly**


2261009	SF-SKBI 31/32	Snap foot, for horizontal or vertical mounting of the SKBI plug-in card blocks, on the NS 35/7.5 DIN rail
---------	---------------	---

SKBI 32/C Order No.: 2261038

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2261038>

## Diagrams/Drawings


### Dimensioned drawing



SKBI 32/C Order No.: 2261038

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2261038>

Schematic diagram



SKBI 32/C Order No.: 2261038

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2261038>

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;